

## TECHNISCHE EIGENSCHAFTEN

TUTELA T. AXLE DRIVE

PRODUKTCODE: 1607

### ANWENDUNG

Full synthetic final drive lubricant with excellent cold flow properties.  
Especially recommended for limited slip differentials with carbon linings.  
High extreme pressure (EP) protection for hypoid axles.  
Good thermal and oxidative stability."

### SPEZIFIZIERUNGEN

SAE 75W-85, API GL 5, FCA 9.55550-DA8 CONTRACTUAL TECHNICAL REF. # F058.N15

### TESTBESCHREIBUNG

TESTBESCHREIBUNG	VERFAHREN	EINHEIT	TYPISCHER WERT
AUSSEHEN	--	--	B&C
DICHTE 15°C	ASTM D 4052	g/cm <sup>3</sup>	0.862
VISCOSITA' @ 100°C	ASTM D 445	cSt	11.5
VISKOSITÄTSINDEX	ASTM D 2270	--	188
Brookfield -40°C	DIN 51398	mPas	38400
STOCKPUNKT	ASTM D 97	°C	-42
VLAMPUNT CI. O. C.	ASTM D 92	°C	222

Alle technischen Daten sind Richtwerte.

FORSCHUNG & ENTWICKLUNG

02/2017