

Product Data Sheet

Revised: 2024/11/08 (version 1.0)

SELENIA GOLD SYNTH 10W-40

SELENIA lubricants have been engineered to take the very best care of your engine's specific needs. With more than 25 years of expertise in fluids and engine technology, we've engineered a range highly advanced lubricants to deliver maximum protection and get the best performance of your vehicle day after day. SELENIA is the lubricant that has paved the way with FCA for 25 years, and today it represents a standard of excellence for everybody.

Description and Applications

SELENIA GOLD SYNTH 10W-40 is a synthetic based lubricant developed to effectively controls the heat, resisting oxidation and preventing oil degradation and deposit build up, to protect parts and maintain engine efficiency for the full drain interval.

Benefits

- Enhanced wear protection for engines with high power performance
- Enhanced friction reduction among mechanical components
- Enhanced maximised engine performance and power output

Approvals, Specifications and Recommendations

Specifications:

- API SN
- ACEA A3/B4

Note: Always consult your owner's manual to check for recommended viscosity grade and specifications for your specific vehicle

Typical Physical Data

Parameters	Method	Unit	Typical Value
Appearance	-	-	Bright & Clear
Density at 15°C	ASTM D4052	g/cm ³	0.8676
Kinematic Viscosity at 100°C	ASTM D445	mm ² /s	14.28
Viscosity Index	ASTM D2270	-	151
Flash Point Cl. O. C.	ASTM D92	°C	226
T.B.N.	ASTM D2896	mgKOH/g	10.57
Pour Point	ASTM 5950	°C	-39

All technical data are provided for reference only. These characteristics are typical of current production. Whilst future production will conform to PLI's specification, variations in these characteristics may occur.

Health, Safety and Environment

This product is unlikely to present any significant health and safety hazards when used in the recommended application. Avoid contact with skin. Wash immediately with soap and water after skin contact. Do not discharge into drains, soil or water.

For further details regarding storage, safe handling, and disposal of product, please refer to product SDS.

Important Note

The word PETRONAS, the PETRONAS logo and such other related trademarks and/or marks used herein are trademarks or registered trademarks of PETRONAS Lubricants International Sdn. Bhd. ("PLISB"), or its subsidiaries or related Holding Corporation under license unless indicated otherwise. The PLI Documents and the information contains herein is believed to be accurate as of the date of printing. PLISB makes no express or implied representation or warranties as to its accuracy or completeness or information in or any transaction performed. The PLI Documents information provided is based on standard tests under laboratory conditions and is given only as a guide. Users are advised to ensure that they refer to the latest version of these PLI Documents. It is the responsibility of the users to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations imposed by the respective local authorities.

Safety Data Sheets are available for all our products and should be only be consulted for appropriate information regarding storage, safe handling and disposal of the product. No responsibility shall be taken by either PLISB or its subsidiaries and related holding corporation for any loss or injury or any direct, indirect, special, exemplary, consequential damages or any damages whatsoever, whether in action of contract, negligence or other tortuous action, in connection or resulting from abnormal use of the materials and/or information, from any failure to adhere to recommendations, or from hazards inherent in the nature of the materials and/or information. All products, services and information supplied are under our standard conditions of sale. Please consult with any of our local representative in the event you require any further information.

Code: 70771

