

Product Data Sheet

Revised: 16/12/2024 (version 1.1)



PETRONAS

PETRONAS Paraflu UP

Designed to be the Fluid Technology Solutions of choice providing excellent protection and longer fluid life for Vehicle cooling systems

Description and Applications

PETRONAS Paraflu UP is a premium performance concentrated Long-Life Coolant delivering optimized performance and component durability for vehicles cooling systems. Formulated with Mono-Ethylene Glycol enhanced with a special Organic Acid salts inhibitor (OAT Technology), free of nitrites, borates, phosphates, silicates and amines, it provides excellent protection against overheating, frost and corrosion and aversive agent (bitrex).

Specifically developed for FCA and IVECO, it is also suitable for passenger cars and commercial vehicles where a OAT coolant technology is required.

Approvals, Specifications and Recommendations

Specifications:

- ASTM D 3306 Type 1
- ASTM D 6210 Type 1-FF
- CUNA 956-16

- Iveco 18-1830 CTR n° I101.M16
- MS.90032
- PSA B71 5110

Approvals

- Fiat 9.55523 CTR n° F101.M01
- MS.50203

Performance Level:

- Chrysler MS 12106
- Lotus Reference PE-00140

Note: Always consult your owner's manual to check recommended viscosity grade and specifications for your specific vehicle

Typical Physical Data

Parameters	Method	Unit	Typical Value
Color	-	-	Red
Relative Density @15°C	ASTM D 1122	g/cm ³	1.123
pH, 50% vol in DI water	ASTM D 1287	-	8,2
Reserve alkalinity	ASTM D 1121	ml	6.4
Boiling point, 50% vol in DI water	ASTM D 1120	°C	109
Freezing point, 50% vol in DI water	ASTM D 1177	°C	-39
Glassware corrosion test	ASTM D1384	-	PASS
Hard water compatibility test	FIAT 50537	-	PASS

All technical data are provided for reference only. These characteristics are typical of current production. Whilst future production will conform to PLI's specification, variations in these characteristics may occur.

Health, Safety and Environment

This product is unlikely to present any significant health and safety hazards when used in the recommended application. Avoid contact with skin. Wash immediately with soap and water after skin contact. Do not discharge into drains, soil or water.

For further detail regarding storage, safe handling, and disposal of product, please refers to product SDS or contact us at: www.pli-petronas.com

Important Note

The word PETRONAS, the PETRONAS logo and such other related trademarks and/or marks used herein are trademarks or registered trademarks of PETRONAS Lubricants International Sdn. Bhd. ("PLISB"), or its subsidiaries or related Holding Corporation under license unless indicated otherwise. The data sheet and the information contained herein is believed to be accurate as of the date of printing. PLISB makes no express or implied representation or warranties as to its accuracy or completeness or information in or any transaction performed. The PLI Documents information provided is based on standard tests under laboratory conditions and is given only as a guide. Users are advised to ensure that they refer to the latest version of these PLI Documents. It is the responsibility of the users to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations imposed by the respective local authorities.

Safety Data Sheets are available for all our products and should be only be consulted for appropriate information regarding storage, safe handling and disposal of the product. No responsibility shall be taken by either PLISB or its subsidiaries and related holding corporation for any loss or injury or any direct, indirect, special, exemplary, consequential damages or any damages whatsoever, whether in action of contract, negligence or other tortious action, in connection or resulting from abnormal use of the materials and/or information, from any failure to adhere to recommendations, or from hazards inherent in the nature of the materials and/or information. All products, services and information supplied are under our standard conditions of sale. Please consult with any of our local representative in the event you require any further information.

Code: 76059