



PETRONAS

TECHNISCHE EIGENSCHAFTEN

ARBOR ALFAPRIME 15W-40

PRODUKTCODE: 3637

ANWENDUNG

Low SAPS lubricant for the new generation low emission engines for tractors, other farming and earthmoving machines, including those equipped with with exhaust gas re-circulation or after treatment systems (EGR, SCR, diesel particulate filter DPF). Suitable for engines with traditional older technology.

SPEZIFIZIERUNGEN

SAE 15W-40, API CJ-4, ACEA E7/E9, Caterpillar ECF-3 / ECF-2 / ECF-1a, CUMMINS CES 20081, DETROIT DIESEL 93K218, DEUTZ DQC III-10-LA, MACK EO-O PREMIUM PLUS-07, MAN M3575, MB-Approval 228.31 Performance, RENAULT RVI RLD-3

TESTBESCHREIBUNG

TESTBESCHREIBUNG	VERFAHREN	EINHEIT	TYPISCHER WERT
AUSSEHEN	--	--	C & B
DICHTE 15°C	ASTM D 4052	g/cm ³	0,878
VISKOSITÄT BEI 100°C	ASTM D 445	cSt	15.4
VISKOSITÄTSINDEX	ASTM D 2270	--	135
TBN	ASTM D 2896	mg KOH/g	9.1
FLAMMPUNKT COC	ASTM D 92	°C	>200
STOCKPUNKT	ASTM D 97	°C	<-27
SCHAUM BEI 24°C	ASTM D 892	cc/s	0 / 0

Alle technischen Daten sind Richtwerte.

FORSCHUNG & ENTWICKLUNG

06/2019