



PETRONAS Urania Elite Long Drain

10W-40

Designed with StrongTech™ technology that is trusted to keep engines in excellent condition and extend their service life

I feel confident and trust that my commercial vehicles will perform reliably, no matter the conditions or load. Seeing my customers happy and satisfied makes me proud of what I've achieved

Description and Applications

PETRONAS Urania Elite Long Drain 10W-40 is a synthetic technology heavy duty engine oil, with extended service interval capabilities, formulated with StrongTech™ technology, that forms a uniquely strong fluid film to protect the engine, retain performance and keep trucks running and available for longer periods. This helps to reduce the total cost of ownership.

Low SAPS oil, suitable for Euro VI and Euro V heavy duty diesel applications including modern, high-output, low emission engines fitted with emission control systems using DPF, SCR, DOC and EGR technologies. It is also suitable for older turbocharged and naturally aspirated diesel engine generations, both on-highway and off-highway, running on high or ultra-low Sulphur diesel and biodiesel (*always refer to your user's manual*).

Suitable for CNG vehicles where specifications listed in this document are recommended.

Approved Daimler Truck Fluid Release (DTFR 15C110 and 15C120), fully backward compatible and suitable for use for vehicles recommending the previous Daimler MB 228.51 and 228.52 specification.

Fully backward compatible with previous E6-16, E7-16 and E9-16 classifications.

PETRONAS Urania Elite Long Drain 10W-40 replaces Urania 5000 LS 10W-40 and Urania 5000 LSE 10W-40

Enhance your vehicle's performance by pairing PETRONAS Urania with PETRONAS Tutela fluids

Benefits

Contributes significantly to reducing your operating costs through:

- **Extended Drain Interval and Engine Life** driven by exceptional thermal and oxidation stability under high temperature, providing viscosity stability and preventing formation of deposits and sludge to prolong oil life even under severe conditions
- **Outstanding protection for emission after-treatment systems** such as DPF and DOC with low ash additive system
- **Effectively combats high concentration of soot build ups, critical to prevent loss of vehicle horsepower**
- **Improved lubrication during start-up** thanks to its low temperature viscosity
- **Optimal viscosity levels and lubrication during service life, to prevent unplanned breakdowns**
- **Better fluid film resistance under severe mechanical stress to deliver enhanced engine durability**

Approvals, Specifications and Recommendations

Specifications:

- API CK-4, API CJ-4
- ACEA E8, E7, E11
- JASO DH-2

Approvals:

- DTFR 15C110
- DTFR 15C120
- Mack EOS-4.5
- MAN M3775
- Renault RLD-3
- Volvo VDS-4.5

Performance Level:

- CAT ECF-3
- Cummins CES 20086, CES 20081
- Detroit Diesel DFS93K222/218
- Deutz DQC IV-18 LA
- DAF PSQL 2.1E LD* *DAF Rapido Service system required
- IVECO 18-1804 Class TLS E9
- IVECO 18-1804 Class TLS CK4
- MAN M3477
- MB 228.51, MB 228.52, MB 228.31
- MTU Oil Category 3.1
- Scania Low Ash
- Volvo VDS-4

Typical Physical Data

Parameters	Method	Unit	Typical Value
Appearance	-	-	Bright & Clear
Density @15°C	ASTM D 4052	g/cm ³	0.869
Kinematic Viscosity @100°C	ASTM D 445	mm ² /s (cSt)	14.2
Viscosity Index	ASTM D 2270	-	149
Flash Point COC	ASTM D 92	°C	> 220
TBN	ASTM D 2896	mgKOH/g	10
CCS at -25°C	ASTM D5293	mPa·s	6200
Pour Point	ASTM D 97	°C	-42

All technical data is provided for reference only. These characteristics are typical of current production. Whilst future production will conform to PLI's specification, variations in these characteristics may occur.

Health, Safety and Environment

This product is unlikely to present any significant health and safety hazards when used in the recommended application. Avoid contact with skin. Wash immediately with soap and water after skin contact. Do not discharge into drains, soil or water. For further detail regarding storage, safe handling, and disposal of product, please refer to product SDS or contact us at: www.pli-petronas.com

Important Note

The word PETRONAS, the PETRONAS logo and such other related trademarks and/or marks used herein are trademarks or registered trademarks of PETRONAS Lubricants International Sdn. Bhd. ("PLISB"), or its subsidiaries or related Holding Corporation under license unless indicated otherwise. The PLI Documents and the information contained herein is believed to be accurate as of the date of printing. PLISB makes no express or implied representation or warranties as to its accuracy or completeness or information in or any transaction performed. The PLI Documents information provided is based on standard tests under laboratory conditions and is given only as a guide. Users are advised to ensure that they refer to the latest version of these PLI Documents. It is the responsibility of the users to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations imposed by the respective local authorities.

Safety Data Sheets are available for all our products and should be only be consulted for appropriate information regarding storage, safe handling and disposal of the product. No responsibility shall be taken by either PLISB or its subsidiaries and related holding corporation for any loss or injury or any direct, indirect, special, exemplary, consequential damages or any damages whatsoever, whether in action of contract, negligence or other tortious action, in connection or resulting from abnormal use of the materials and/or information, from any failure to adhere to recommendations, or from hazards inherent in the nature of the materials and/or information. All products, services and information supplied are under our standard conditions of sale. Please consult with any of our local representative in the event you require any further information.