

PETRONAS GEO NG 40

Premium Performance Natural Gas Engine Oil

PETRONAS GEO NG 40 is a premium performance natural gas engine oil specially developed for the lubrication of a wide range of spark-ignited gas-fuelled engines to improve fuel-efficiency and reduce emissions.

Formulated with high quality selected mineral base oils enhanced with advanced anti-wear, antioxidant, detergent, dispersant, anti-rust and anti-foam additives, PETRONAS GEO NG oil provides excellent cleanliness to avoid piston deposit, sludge, and ash control, excellent TBN retention and thermal stability as well as resistance to oxidation/nitration.

PETRONAS GEO NG 40 oil meets or exceeds key OEM requirements.

Applications

PETRONAS GEO NG 40 oil is recommended for use in:

- medium to high speed four-cycle engines requiring a low ash oil
- engines experiencing valve face and seat wear
- lean-burn and stoichiometric four-cycle engines
- engines equipped with catalytic converters
- applications using alternate fuels containing low levels of sulfur or chlorine

Features and Benefits

Features	Benefits
Excellent resistance to sludging	Excellent piston and engine cleanliness for long, efficient operation and reduced overhaul costs
High anti-wear and anti-scuff protection	Protects engine from excessive wear and scuffing, providing long engine life
Excellent detergent and dispersant performance	Protects valve train components, reduces ash and carbon deposits on pistons and combustion chambers
Excellent oxidation and nitration stability	Excellent oxidation and nitration resistance minimize oil thickening particularly under liner air/fuel and maintains oil filter efficiency
High rust & corrosion protection	Inhibits the corrosion process that occurs in presence of acid formation, improving engine life
High foam stability	High efficiency in avoiding foam formation

PETRONAS GEO NG 40

Premium Performance Natural Gas Engine Oil

Typical Properties

Characteristic	Method	Specification	SAE 40
Specific Gravity @15°C	ASTM D 4052	(1)	0,876
Kinematic Viscosity at 40°C, cSt	ASTM D 445	(1)	121,80
Kinematic Viscosity at 100°C, cSt	ASTM D 445	(1)	13,48
Viscosity Index	ASTM D 2270	(1)	106
Flash Point, °C	ASTM D 92	(1)	270
Pour Point, °C	ASTM D 97	(1)	-30
TAN, mgKOH/g	ASTM D 664	(1)	0,42
TBN, mgKOH/g	ASTM D2896	(1)	5,38
Sulphated Ash, %	ASTM D874	(1)	0,48
Foam Sequence I, mL	ASTM D 892	(1)	0/0

All technical data are provided for reference only / (1): not required in specification / SS is available upon request including quality control limits

Performance Levels

- Caterpillar CG132, CG132B, CG170, CG170B, and CG260
- GE Jenbacher Class A & B gases, Type 2, 3, 4 and 6 engines
- MAN (M 3271-2)
- MWM TR-0199-99-2015 (TCG 2016, TCG 3016, TCG 2020, TCG 3020, TCG 2032 and TCG 2032B)
- Rolls Royce B35:40, C26:33 and K-G1, G2, G3 and G4 engines
- Wartsila 175SG, 220SG, 25SG, 28SG, 34SG, 50SG, 20DF, 32DF, 34DF and 50DF

PETRONAS GEO NG 40

Premium Performance Natural Gas Engine Oil

Health, Safety and Environment

This product is unlikely to present any significant health and safety hazards when used in the recommended application. Avoid contact with skin. Wash immediately with soap and water after skin contact. Do not discharge into drains, soil or water.

For further detail regarding storage, safe handling, and disposal of product, please refer to product SDS or contact us at: www.pli-petronas.com.

Important Note

The word PETRONAS, the PETRONAS logo and such other related trademarks and/or marks used herein are trademarks or registered trademarks of PETRONAS Lubricants International Sdn. Bhd. ("PLISB"), or its subsidiaries or related Holding Corporation under license unless indicated otherwise. The PLI Documents and the information contained herein are believed to be accurate as of the date of printing. PLISB makes no express or implied representation or warranties as to its accuracy or completeness or information in or any transaction performed. The PLI Documents and information provided are based on standard tests under laboratory conditions and is given only as a guide. Users are advised to ensure that they refer to the latest version of these PLI Documents. It is the responsibility of the users to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations imposed by the respective local authorities.

Safety Data Sheets are available for all our products and should only be consulted for appropriate information regarding storage, safe handling and disposal of the product. No responsibility shall be taken by either PLISB or its subsidiaries and related holding corporation for any loss or injury or any direct, indirect, special, exemplary, consequential damages or any damages whatsoever, whether in action of contract, negligence or other tortuous action, in connection with or resulting from abnormal use of the materials and/or information, from any failure to adhere to recommendations, or from hazards inherent in the nature of the materials and/or information. All products, services and information supplied are under our standard conditions of sale. Please consult with any of our local representatives in the event you require any further information.