

PETRONAS DISROL 12 HS SERIES

High Performance 12 TBN High Speed Oil for Diesel Engine

PETRONAS Disrol 12 HS Series are high performance, medium and high speed oil specially developed for diesel engine (marine or stationary service) burning distillate fuels or light fuels blends with sulfur content up to 1,0% operating under severe conditions.

Formulated with high quality selected base oils enhanced with anti-wear, detergent/dispersant, anti-oxidant, anti-rust and anti-foam additives, PETRONAS Disrol 12 HS oil provides excellent engine cleanliness, especially in crankcase and camshaft areas, excellent oxidation resistance, thermal stability, low volatility and high wear and corrosion protection.

Applications

PETRONAS Disrol 12 HS Series are recommended for use in:

- medium and high speed trunk piston engines operating on distillate fuels or light fuels blends
- large crosshead type diesel engines operating up to 1,0% sulfur fuels

Features and Benefits

Features	Benefits		
High anti-wear protection	High protection against excessive piston rings and cylinder linear wear		
High detergency/dispersancy	High engine cleanliness by effectively controlling varnish, lacquer and other common engine deposits and reduces maintenance cost		
Excellent deposit control	Keep clean areas such as piston under crown and piston ring belt area enabling piston rings to function efficiently to maintain high power output and engine efficiency		
Excellent thermal and oxidation stability	Maintains performance levels under high temperatures to ensure long oil life and possess good oil consumption control		
TBN retention	High protection against corrosion up to 1,0% sulphur fuels		

Typical Properties

Characteristic	Method	SAE 30	SAE 40
Specific Gravity @15°C	ASTM D 4052	0,889	0,897
Kinematic Viscosity at 40°C, cSt	ASTM D 445	83,85	153,4
Kinematic Viscosity at 100°C, cSt	ASTM D 445	10,52	14,98
Viscosity Index	ASTM D 2270	109	97
Flash Point, °C	ASTM D 92	250	250
Pour Point, °C	ASTM D 97	-15	-9
TBN, mgKOH/g	ASTM D 2896	12	12
Sulphated Ash, %wt	ASTM D 874	1,6	1,6

ALL RIGHTS RESERVED. THIS PRODUCT DATA SHEET (INCLUDING NAME, INFORMATION, LOGOS, IMAGES, PICTURES AND ICONS) WHICH RELATES OR REFERS TO PETRONAS LUBRICANTS INTERNATIONAL (PLI) IS THE SOLE AND ABSOLUTE PROPERTY OF PLI AND/OR ITS HOLDING COMPANY AND SHALL BE TREATED AS PRIVATE AND CONFIDENTIAL. NO PART OF THIS DOCUMENT MAY BE REPRODUCED, STORED IN A RETRIEVAL SYSTEM OR TRANSMITTED IN ANY FORM OR ANY MEANS (ELECTRONIC, MECHANICAL, RECORDING OR OTHERWISE) WITHOUT THE PERMISSION OF PLI AND/OR ITS HOLDING COMPANY.



PETRONAS DISROL 12 HS SERIES

High Performance 12 TBN High Speed Oil for Diesel Engine

All technical data are provided for reference only and all specification based on SAE J300 / SS is available upon request including quality control limits

Health, Safety and Environment

This product is unlikely to present any significant health and safety hazards when used in the recommended application. Avoid contact with skin. Wash immediately with soap and water after skin contact. Do not discharge into drains, soil or water.

For further detail regarding storage, safe handling, and disposal of product, please refer to product SDS or contact us at: <u>www.pli-petronas.com</u>.

Important Note

The word PETRONAS, the PETRONAS logo and such other related trademarks and/or marks used herein are trademarks or registered trademarks of PETRONAS Lubricants International Sdn. Bhd. ("PLISB"), or its subsidiaries or related Holding Corporation under license unless indicated otherwise. The PLI Documents and the information contained herein are believed to be accurate as of the date of printing. PLISB makes no express or implied representation or warranties as to its accuracy or completeness or information in or any transaction performed. The PLI Documents and information provided are based on standard tests under laboratory conditions and is given only as a guide. Users are advised to ensure that they refer to the latest version of these PLI Documents. It is the responsibility of the users to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations imposed by the respective local authorities.

Safety Data Sheets are available for all our products and should only be consulted for appropriate information regarding storage, safe handling and disposal of the product. No responsibility shall be taken by either PLISB or its subsidiaries and related holding corporation for any loss or injury or any direct, indirect, special, exemplary, consequential damages or any damages whatsoever, whether in action of contract, negligence or other tortuous action, in connection with or resulting from abnormal use of the materials and/or information, from any failure to adhere to recommendations, or from hazards inherent in the nature of the materials and/or information. All products, services and information supplied are under our standard conditions of sale. Please consult with any of our local representatives in the event you require any further information.

ALL RIGHTS RESERVED. THIS PRODUCT DATA SHEET (INCLUDING NAME, INFORMATION, LOGOS, IMAGES, PICTURES AND ICONS) WHICH RELATES OR REFERS TO PETRONAS LUBRICANTS INTERNATIONAL (PLI) IS THE SOLE AND ABSOLUTE PROPERTY OF PLI AND/OR ITS HOLDING COMPANY AND SHALL BE TREATED AS PRIVATE AND CONFIDENTIAL. NO PART OF THIS DOCUMENT MAY BE REPRODUCED, STORED IN A RETRIEVAL SYSTEM OR TRANSMITTED IN ANY FORM OR ANY MEANS (ELECTRONIC, MECHANICAL, RECORDING OR OTHERWISE) WITHOUT THE PERMISSION OF PLI AND/OR ITS HOLDING COMPANY.