



PETRONAS

Technical Data Sheet

Revised: 2017/06/27 (version 1.0)

PETRONAS Sprinta T900

APPLICATIONS

Suitable for all types of 2-Stroke gasoline motorcycle engines especially for newer generation engines with carburetor, electronic fuel injector (EFI) and direct fuel injector (DFI), from racing, endurance, motocross, go-carts, on-road and even off-road riding conditions. It is suitable for motorcycles manufactured by leading Japanese, European and American manufacturers operating under normal to severe riding conditions.

Note: Always consult your owner's manual to check recommended viscosity grade and specifications for your particular vehicle.

SPECIFICATIONS & APPROVALS*

Meets or Exceeds the requirements of:	API TC
	JASO FD
	ISO EGD

* All technical data is provided for reference only.

TYPICAL PHYSICAL DATA**

Parameters	Method	Unit	Typical Value
Appearance	-	-	B&C
Density 15⁰C	ASTM D 4052	g/cm ³	0.878
Viscosity at 100⁰C	ASTM D 445	cSt	11.0
Viscosity Index	ASTM D 2270	-	159
Flash Point Cl. O. C	ASTM D 92	⁰ C	120
Pour point	ASTM D 97	⁰ C	-48
Sulphated Ash	ASTM D 874	%	0.15

** These characteristics are typical of current production. Whilst future production will conform to PLI's specification, variations in these characteristics may occur.

FEATURES & BENEFITS

- Exceptional oil film strength ensuring efficient protection and ultimate lubrication at high temperature and RPMs, delivering improved acceleration
- Exceptional protection against ring-sticking and engine seizure, helps prolong engine life.
- Exceptional detergency control to eliminate damaging deposits, protecting engines against exhaust system blocking.
- Low-ash technology effectively reduce pre-ignition and catalyst deterioration, helps delivering exceptional engine efficiency and power.
- Optimum clean and efficient burning produces extremely low exhaust smoke
- Exceptional cold temperature performance.
- Exceptional mixing with leaded and unleaded petrol.

OIL TYPE

- Fully Synthetic

Health, Safety and Environment

This product is unlikely to present any significant health and safety hazards when used in the recommended application. Avoid contact with skin. Wash immediately with soap and water after skin contact. Do not discharge into drains, soil or water.

For further detail regarding storage, safe handling, and disposal of product, please refer to product SDS or contact us at: www.pli-petronas.com

Important Note

The word PETRONAS, the PETRONAS logo and such other related trademarks and/or marks used herein are trademarks or registered trademarks of PETRONAS Lubricants International Sdn. Bhd. ("PLISB"), or its subsidiaries or related Holding Corporation under license unless indicated otherwise. The PLI Documents and the information contained herein is believed to be accurate as of the date of printing. PLISB makes no express or implied representation or warranties as to its accuracy or completeness or information in or any transaction performed. The PLI Documents information provided is based on standard tests under laboratory conditions and is given only as a guide. Users are advised to ensure that they refer to the latest version of these PLI Documents. It is the responsibility of the users to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations imposed by the respective local authorities.

Safety Data Sheets are available for all our products and should be only be consulted for appropriate information regarding storage, safe handling and disposal of the product. No responsibility shall be taken by either PLISB or its subsidiaries and related holding corporation for any loss or injury or any direct, indirect, special, exemplary, consequential damages or any damages whatsoever, whether in action of contract, negligence or other tortious action, in connection or resulting from abnormal use of the materials and/or information, from any failure to adhere to recommendations, or from hazards inherent in the nature of the materials and/or information. All products, services and information supplied are under our standard conditions of sale. Please consult with any of our local representative in the event you require any further information.

Code: 2043