

PETRONAS CIRCULA MILL

High Performance Circulating Oil

PETRONAS Circula Mill is high performance circulating oil specially developed for steel mill equipment where MORGOIL® lubricant is recommended.

Formulated with high quality selected mineral base oils enhanced with advanced anti-oxidant, anti-rust and anti-foam additives, PETRONAS Circula Mill oil provides excellent water separability*, high rust and corrosion protection and very good oxidation stability for longer lasting performance.

PETRONAS Circula Mill meet the MORGOIL® Advanced Lubricant Specification.

*better performance compared to typical industrial standards for MORGOIL® Lubricant Specification based on UEC Dynamic Demulsibility Endurance Test.

Applications

PETRONAS Circula Mill is recommended for use in:

- MORGOIL® circulating systems requiring high quality circulating oils

Features & Benefits

Features	Benefits
Excellent water separability	Due to excellent water separability the system is protected from water degenerative effects, maintaining circulating system efficiency at required level and reducing maintenance costs
Very good oxidation stability	Maintains performance levels under regular temperatures and pressure
High rust & corrosion protection	Inhibits the corrosion process that occurs in presence of water, improving equipment life
Excellent foam stability	Maintains excellent efficiency in circulating systems, ensures smooth operation. Protects the system from air degenerative effects reducing maintenance costs
High multi metal compatibility	Compatible with most metal alloys ensuring trouble free performance of the system
Very good compatibility with most seal and elastomers	Compatible with most seals and elastomers, which prevents oil leaks and contamination due to seal erosion



PETRONAS

Technical Data Sheet

Version 2.0_20.09.2018

PETRONAS CIRCULA MILL

High Performance Circulating Oil

Typical Properties

Characteristic	Method	Specification	460	680
Specific Gravity @15°C	ASTM D 4052	(1)	0,898	0,904
Kinematic Viscosity at 40°C, cSt	ASTM D 445	±10%	460	680
Kinematic Viscosity at 100°C, cSt	ASTM D 445	±10%	31,3	42,0
Viscosity Index	ASTM D 2270	Min. 90	98	103
Flash Point, °C	ASTM D 92	Min. 195	230	234
Pour Point, °C	ASTM D 97	(1)	-12	-9
TAN, mgKOH/g	ASTM D 664	Report	0,05	0,05
Water Separability, 40/37/3 - mins	ASTM D 1401	(1)	10	10
Dynamic Demulsibility Endurance, %				
- % water in oil after centrifuging	Run at Clark Labs	Max. 10%	9%	8%
- % oil in water after centrifuging		Max. 1%	0%	0%
Copper Strip Corrosion	ASTM D 130	Max. 1	1b	1b
Foam Sequence I, mL		50/0	0/0	0/0
Foam Sequence II, mL	ASTM D 892	50/0	0/0	0/0
Foam Sequence III, mL		50/0	0/0	0/0

All technical data is provided for reference only and all specification based on MORGOIL® Advanced Lubricant Specification
(1): not required in the specification / SS is available upon request including quality control limits

Performance Levels

- MORGOIL® Advanced Lubricant Specification

www.pu-petronas.com

ALL RIGHTS RESERVED. THIS PRODUCT DATA SHEET (INCLUDING NAME, INFORMATION, LOGOS, IMAGES, PICTURES AND ICONS) WHICH RELATES OR REFERS TO PETRONAS LUBRICANTS INTERNATIONAL (PLI) IS THE SOLE AND ABSOLUTE PROPERTY OF PLI AND/OR ITS HOLDING COMPANY AND SHALL BE TREATED AS PRIVATE AND CONFIDENTIAL. NO PART OF THIS DOCUMENT MAY BE REPRODUCED, STORED IN A RETRIEVAL SYSTEM OR TRANSMITTED IN ANY FORM OR ANY MEANS (ELECTRONIC, MECHANICAL, RECORDING OR OTHERWISE) WITHOUT THE PERMISSION OF PLI AND/OR ITS HOLDING COMPANY.

PETRONAS CIRCULA MILL

High Performance Circulating Oil

Health, Safety and Environment

This product is unlikely to present any significant health and safety hazards when used in the recommended application. Avoid contact with skin. Wash immediately with soap and water after skin contact. Do not discharge into drains, soil or water.

For further detail regarding storage, safe handling, and disposal of product, please refer to product SDS or contact us at: www.pli-petronas.com

Important Note

The word PETRONAS, the PETRONAS logo and such other related trademarks and/or marks used herein are trademarks or registered trademarks of PETRONAS Lubricants International Sdn. Bhd. ("PLISB"), or its subsidiaries or related Holding Corporation under license unless indicated otherwise. The PLI Documents and the information contained herein is believed to be accurate as of the date of printing. PLISB makes no express or implied representation or warranties as to its accuracy or completeness or information in or any transaction performed. The PLI Documents information provided is based on standard tests under laboratory conditions and is given only as a guide. Users are advised to ensure that they refer to the latest version of these PLI Documents. It is the responsibility of the users to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations imposed by the respective local authorities.

Safety Data Sheets are available for all our products and should be only be consulted for appropriate information regarding storage, safe handling and disposal of the product. No responsibility shall be taken by either PLISB or its subsidiaries and related holding corporation for any loss or injury or any direct, indirect, special, exemplary, consequential damages or any damages whatsoever, whether in action of contract, negligence or other tortious action, in connection or resulting from abnormal use of the materials and/or information, from any failure to adhere to recommendations, or from hazards inherent in the nature of the materials and/or information. All products, services and information supplied are under our standard conditions of sale. Please consult with any of our local representative in the event you require any further information.