

TECHNISCHE EIGENSCHAPPEN

MULTI F

ARTIKELCODE: 2695

TOEPASSING

Multi-purpose transmission oil (U.T.T.O) for use on tractor transmissions and hydraulic systems in gearboxes, rear transmissions with oil immersed brakes, side final drives, wheel final drives, differentials, hydraulic systems, drive pulleys, mechanical and hydrostatic drives.

SPECIFICATIES

SAE 20W-30, NH 420 A, API GL 4, ISO VG 46/68

OMSCHRIJVING TEST

OMSCHRIJVING TEST	METHODE	EENHEID	TYPISCHE WAARDE
VOORKOMEN	--	--	B. & C.
KLEUR	--	--	L 3
DENSITEIT @ 15°C	ASTM D 4052	g/cm ³	0,888
VISCOSITEIT @ 40°C	ASTM D 445	cSt	84
VISCOSITEIT @ 100°C	ASTM D 445	cSt	10,6
VISCOSITEITINDEX	ASTM D 2270	--	111
COPPER CORROSION (3h/150°C)	ASTM D 130	--	1A
VLAMPUNT Cl. O. C.	ASTM D 92	°C	224
STOLPUNT	ASTM D 97	°C	<- 27
SCHUIM @ 24°C	ASTM D 892	cc/s	0

Alle technische informatie wordt als referentie gegeven.

ONDERZOEK & ONTWIKKELING

11/2010