

**PETRONAS**

PETRONAS Tutela Brake Fluid DOT 3

Designed to be the Fluid Technology Solutions of choice providing excellent protection and longer fluid life for braking and clutch systems

Description and Applications

PETRONAS Tutela Brake Fluid DOT 3 is a high-quality performance hydraulic brake and clutch systems fluid, delivering optimized performance and component durability for Vehicles braking systems.

Benefits

PETRONAS Tutela Brake Fluid DOT 3 enhances your vehicle performances while significantly reducing your operating costs through:

- **Long Braking System Life** driven by:
 - o Enhanced corrosion protection to protect metal-based components.
 - o Good thermal stability to deliver stable fluid performances during the service life.
 - o Effective lubricity to prevent squeak noise and improve the system reaction time.
 - o Elastomer and rubber compatibility to prevent fluid leakages and longer component's life

Provides outstanding Driving Experience through:

- **Enhanced pedal run stability** due to no hysteresis in cold/hot/cold condition
- **Good prevention against brake system fading** even in the most severe conditions thanks to its high thermal resistance.
- **Boiling point** to prevent vapor lock conditions and improve braking efficiency.

Approvals, Specifications and Recommendations

Specifications:

- FMVSS No. 116 DOT 3
- ISO 4925 Class 3
- SAE J 1703

Performance Level:

- Continental ATE N553 11 05
- FCA 9.55597

Note: Always consult your owner's manual to check recommended viscosity grade and specifications for your specific vehicle;

WARNING: PETRONAS Tutela Brake Fluid DOT 3 should never be used in place of or mixed with silicone-based brake fluids (DOT 5) nor should be used where DOT 5.1 fluids are prescribed.

Typical Physical Data

Parameters	Method	Unit	Typical Value
Color	-	-	Yellow
Relative Density @20°C	ASTM D 5931	g/cm ³	1.035
Kinematic Viscosity @100°C	ASTM D 445	mm ² /s (cSt)	2.10
Kinematic Viscosity @-40°C	ASTM D 445	mm ² /s (cSt)	1240
Boiling Point	ASTM D 1120	°C	248
Wet Boiling Point	ASTM D 1120	°C	150
Effect on Rubber SBR	ISO 4925	-	PASS
Effect on Rubber EPDM	SAE J 1703	-	PASS
Effect on Rubber Natural	ISO 4925	-	PASS

All technical data is provided for reference only. These characteristics are typical of current production. Whilst future production will conform to PLI's specification, variations in these characteristics may occur.

Health, Safety and Environment

This product is unlikely to present any significant health and safety hazards when used in the recommended application. Avoid contact with skin. Wash immediately with soap and water after skin contact. Do not discharge into drains, soil or water.

For further detail regarding storage, safe handling, and disposal of product, please refer to product SDS or contact us at: www.pli-petronas.com

Important Note

The word PETRONAS, the PETRONAS logo and such other related trademarks and/or marks used herein are trademarks or registered trademarks of PETRONAS Lubricants International Sdn. Bhd. ("PLISB"), or its subsidiaries or related Holding Corporation under license unless indicated otherwise. The PLI Documents and the information contained herein is believed to be accurate as of the date of printing. PLISB makes no express or implied representation or warranties as to its accuracy or completeness or information in or any transaction performed. The PLI Documents information provided is based on standard tests under laboratory conditions and is given only as a guide. Users are advised to ensure that they refer to the latest version of these PLI Documents. It is the responsibility of the users to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations imposed by the respective local authorities.

Safety Data Sheets are available for all our products and should be only be consulted for appropriate information regarding storage, safe handling and disposal of the product. No responsibility shall be taken by either PLISB or its subsidiaries and related holding corporation for any loss or injury or any direct, indirect, special, exemplary, consequential damages or any damages whatsoever, whether in action of contract, negligence or other tortious action, in connection or resulting from abnormal use of the materials and/or information, from any failure to adhere to recommendations, or from hazards inherent in the nature of the materials and/or information. All products, services and information supplied are under our standard conditions of sale. Please consult with any of our local representative in the event you require any further information.

Code: 76232