

TECHNICAL CHARACTERISTICS

TOP EVO

PRODUCT CODE: 4196

APPLICATION

High boiling point Brake fluid based on glycolethers and boric esters for heavy duty hydraulic brake system combined with ABS, TSC ESP/DSC.

SPECIFICATIONS

SAE J1703, SAE J1704, ISO 4925 Class 6, FMVSS No.116 - DOT3, DOT4, DOT5.1, JIS K2233, FIAT 9.55597 C.T.R. N°F002.L18

TEST DESCRIPTION

TEST DESCRIPTION	METHOD	UNIT	TYPICAL VALUE
ASPECT	--	--	CLEAR
COLOUR	--	--	LIGHT YELLOW
DENSITY 20° C	ASTM D5931	g/cm ³	1,06
VISCOSITA' @ 100°C	ASTM D 445	cSt	> 1,5
VISCOSITY @ -40°C	ASTM D 445	cSt	< 700
BOILING POINT	ISO 4925	°C	> 265
WET BOILING POINT	ISO 4925	°C	> 180
EFFECT ON RUBBER SBR	ISO 4925	--	PASS
EFFECT ON RUBBER EPDM	SAE J 1703	--	PASS
EFFECT ON RUBBER NATURAL	ISO 4925	--	PASS

All technical data is provided for reference only.