

PETRONAS GEO BLG 40

Premium Performance Bio and Landfill Gas Engine Oil

PETRONAS GEO BLG 40 is a premium performance bio and landfill gas engine oil specially developed for bio and landfill applications.

Formulated with the highest quality selected mineral base oils enhanced with advanced anti-wear, antioxidant, detergent, dispersant, anti-rust and anti-foam additives, PETRONAS GEO BLG oil provides excellent anti-wear protection, excellent TBN retention, reduced combustion chamber deposits, low oil consumption and extra protection against landfill gas*.

PETRONAS GEO BLG 40 meet or exceed key OEM requirements.

*Landfill gases are essentially composed of methane and contain a lot of impurities like halogens, siloxane and sulphur, which can harm gas engines.

Applications

PETRONAS Geo BLG 40 oil is recommended for use in:

- landfill gas engines containing moderate levels of halogens, siloxanes and sulphur
- spark ignited four-stroke cycle gas engines where low oil consumption is required
- high output landfill gas engines operating at or more than rated capacity under high temperatures

Features and Benefits

Features	Benefits
High resistance to sludging	High piston and engine cleanliness for long, efficient operation and reduced overhaul costs
Excellent anti-wear and anti-scuff protection	Protects engine from excessive wear and scuffing, providing long equipment life
Excellent detergent and dispersant performance	Protects valve train components, reduces ash and carbon deposits in combustion chambers and neutralizes formation of acids in the oil
High oxidation and nitration stability	High oxidation and nitration which minimizes oil thickening particularly under liner air/fuel ratios and resist oil filter blockage
High rust & corrosion protection	Inhibits the corrosion process that occurs in presence of acid formation, improving engine life
High foam stability	High efficiency in avoiding foam formation

PETRONAS GEO BLG 40

Premium Performance Bio and Landfill Gas Engine Oil

Typical Properties

Characteristic	Method	Specification	SAE 40
Specific Gravity @15°C	ASTM D 4052	(1)	0,874
Kinematic Viscosity at 40°C, cSt	ASTM D 445	(1)	119,30
Kinematic Viscosity at 100°C, cSt	ASTM D 445	(1)	13,31
Viscosity Index	ASTM D 2270	(1)	107
Flash Point, °C	ASTM D 92	(1)	270
Pour Point, °C	ASTM D 97	(1)	-33
TAN, mgKOH/g	ASTM D 664	(1)	0,96
TBN, mgKOH/g	ASTM D2896	(1)	4,51
Sulphated Ash, %	ASTM D874	(1)	0,50
Foam Sequence I, mL	ASTM D 892	(1)	0/0

All technical data are provided for reference only / (1): not required in specification / SS is available upon request including quality control limits

Performance Levels

- CATERPILLAR CG gas engines 3500
- INNIO Jenbacher Class B & C gases, Type 2, 3, 4 and 6 engines
- MAN (M3271-4 & M3271-5)
- MWM TCG gas engines (All TCG engines)

PETRONAS GEO BLG 40

Premium Performance Bio and Landfill Gas Engine Oil

Health, Safety and Environment

This product is unlikely to present any significant health and safety hazards when used in the recommended application. Avoid contact with skin. Wash immediately with soap and water after skin contact. Do not discharge into drains, soil or water.

For further detail regarding storage, safe handling, and disposal of product, please refer to product SDS or contact us at: www.pli-petronas.com.

Important Note

The word PETRONAS, the PETRONAS logo and such other related trademarks and/or marks used herein are trademarks or registered trademarks of PETRONAS Lubricants International Sdn. Bhd. ("PLISB"), or its subsidiaries or related Holding Corporation under license unless indicated otherwise. The PLI Documents and the information contained herein are believed to be accurate as of the date of printing. PLISB makes no express or implied representation or warranties as to its accuracy or completeness or information in or any transaction performed. The PLI Documents and information provided are based on standard tests under laboratory conditions and is given only as a guide. Users are advised to ensure that they refer to the latest version of these PLI Documents. It is the responsibility of the users to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations imposed by the respective local authorities.

Safety Data Sheets are available for all our products and should only be consulted for appropriate information regarding storage, safe handling and disposal of the product. No responsibility shall be taken by either PLISB or its subsidiaries and related holding corporation for any loss or injury or any direct, indirect, special, exemplary, consequential damages or any damages whatsoever, whether in action of contract, negligence or other tortuous action, in connection with or resulting from abnormal use of the materials and/or information, from any failure to adhere to recommendations, or from hazards inherent in the nature of the materials and/or information. All products, services and information supplied are under our standard conditions of sale. Please consult with any of our local representatives in the event you require any further information.