

# Product Data Sheet

Revised: 2021/11/03 (version 1.0)



PETRONAS

## PETRONAS Tutela Coolant LL Premix

Designed to be the Fluid Technology Solutions of choice providing excellent protection and longer fluid life for Vehicle cooling systems

### Description and Applications

PETRONAS Tutela Coolant LL Premix is a premium performance ready to use Long-Life Coolant delivering optimized performance and component durability for vehicles cooling systems. Formulated with Mono-Ethylene Glycol enhanced with a special Organic Acid salts inhibitor (OAT Technology), free of nitrites, borates, phosphates, silicates and amines, it provides excellent protection against overheating, frost and corrosion. Thanks to its wide OEMs coverage, it is suitable for most European, Americans and Asian passenger cars, commercial vehicles and agriculture machineries.

### Benefits

PETRONAS Tutela Coolant LL Premix enhances your vehicle availability while significantly reducing your operating costs through:

- **Long Life Technology** to extend the fluid service life, preventing from deposit formation
- **Extended Cooling System Life** driven by:
  - o Excellent corrosion resistance to protect metal-based components
  - o Enhanced protection against freezing when outside temperature is down to -38°C (-36.4°F)\*
  - o Enhanced protection against boiling in case of circuit temperature up to 125°C (257°F)\*
  - o Very good elastomer and plastic compatibility for a longer component's life

Provides outstanding Driving Experience through:

- **Excellent heat transfer properties to prevent overheating**

\*With 1 bar (15 psi) radiator cap

### Approvals, Specifications and Recommendations

#### Specifications:

- AFNOR NFR 15-601
- AS 2108-2004
- ASTM D 3306
- ASTM D 6210
- BS 6580:2010
- CUNA 956-16
- ONORM V 5123
- SAE J1034
- SANS 1251:2005
- SH 0521-1999

#### Performance Level:

- CNHi MAT 3724
- CNHi MAT 3624
- DAF (MAT 74002)
- Daimler/Mercedes-Benz 325.3
- Fiat 9.55523
- IVECO 18-1830
- MAN 324 Type SNF
- MTU MTL 5048
- Porsche from MY 1996 to MY 2010
- PSA B71 5110
- VW/Audi/Seat/Skoda TL 774-D/F

Note: Always consult your owner's manual to check recommendation for your specific vehicle

### Typical Physical Data

Parameters	Method	Unit	Typical Value
Color	-	-	Pink
Relative Density @15°C	ASTM D 1122	g/cm <sup>3</sup>	1.065
pH	ASTM D 1287	-	8.5
Reserve alkalinity	ASTM D 1121	ml	7.3
Boiling point	ASTM D 1120	°C	108
Freezing point	ASTM D 1177	°C	<-38
Glassware corrosion test	ASTM D1384	-	PASS

All technical data are provided for reference only. These characteristics are typical of current production. Whilst future production will conform to PLI's specification, variations in these characteristics may occur.

### **Health, Safety and Environment**

This product is unlikely to present any significant health and safety hazards when used in the recommended application. Avoid contact with skin. Wash immediately with soap and water after skin contact. Do not discharge into drains, soil or water.

For further detail regarding storage, safe handling, and disposal of product, please refer to product SDS or contact us at: [www.pli-petronas.com](http://www.pli-petronas.com)

### **Important Note**

The word PETRONAS, the PETRONAS logo and such other related trademarks and/or marks used herein are trademarks or registered trademarks of PETRONAS Lubricants International Sdn. Bhd. ("**PLISB**"), or its subsidiaries or related Holding Corporation under license unless indicated otherwise. The data sheet and the information contained herein is believed to be accurate as of the date of printing. PLISB makes no express or implied representation or warranties as to its accuracy or completeness or information in or any transaction performed. The PLI Documents information provided is based on standard tests under laboratory conditions and is given only as a guide. Users are advised to ensure that they refer to the latest version of these PLI Documents. It is the responsibility of the users to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations imposed by the respective local authorities.

Safety Data Sheets are available for all our products and should be only be consulted for appropriate information regarding storage, safe handling and disposal of the product. No responsibility shall be taken by either PLISB or its subsidiaries and related holding corporation for any loss or injury or any direct, indirect, special, exemplary, consequential damages or any damages whatsoever, whether in action of contract, negligence or other tortious action, in connection or resulting from abnormal use of the materials and/or information, from any failure to adhere to recommendations, or from hazards inherent in the nature of the materials and/or information. All products, services and information supplied are under our standard conditions of sale. Please consult with any of our local representative in the event you require any further information.

Code: 81038