

PETRONAS GREASE Ca 00

Calcium Grease

PETRONAS Grease Ca 00 is a calcium grease specially developed for machine tools used in mining operations.

Formulated with selected mineral base oils enhanced with advanced Calcium 12-hydroxystearate soap, anti-oxidant, anti-rust and corrosion inhibitors additives. PETRONAS Grease Ca 00 provides a high level of protection preventing metal to metal contact between the components of the percussion mechanism. This lubricant is designed to be operated through conventional lubricators to control the grease feed rate into the machine.

Applications

PETRONAS Grease Ca 00 is recommended for use in:

• Pneumatic machine tools and rock drills used in mining operations

Note: PETRONAS Grease Ca 00 is recommended for operating temperature range of 0° C to +60°C.

Features and Benefits

Features	Benefits		
Excellent rust & corrosion protection	Protects component surfaces against corrosion, even when the grease is contaminated with water		
High resistance to water wash-out	Equipment protection and good lubrication even in presence of water		
High oxidation stability	Has a high resistance to oxidation when exposed to high temperature and pressure in the percussion mechanisms and does not form deposits		
Controlled grease consumption	The grease consumption can be controlled when fed through most conventional rock drill lubricators		

ALL RIGHTS RESERVED. THIS PRODUCT DATA SHEET (INCLUDING NAME, INFORMATION, LOGOS, IMAGES, PICTURES AND ICONS) WHICH RELATES OR REFERS TO PETRONAS LUBRICANTS INTERNATIONAL (PLI) IS THE SOLE AND ABSOLUTE PROPERTY OF PLI AND/OR ITS HOLDING COMPANY AND SHALL BE TREATED AS PRIVATE AND CONFIDENTIAL. NO PART OF THIS DOCUMENT MAY BE REPRODUCED, STORED IN A RETRIEVAL SYSTEM OR TRANSMITTED IN ANY FORM OR ANY MEANS (ELECTRONIC, MECHANICAL, RECORDING OR OTHERWISE) WITHOUT THE PERMISSION OF PLI AND/OR ITS HOLDING COMPANY.



Technical Data Sheet Revision Date: 28.08.2019

PETRONAS GREASE Ca 00

Calcium Grease

Typical Properties

Characteristic	Method	Specification	Ca 00
Thickener Type	-	Calcium	Calcium
NLGI	ASTM D217	00	00
Color	Visual	Brown	Brown
Unworked Penetration, mm/10	ASTM D217	400 - 430	410
Oil Separation, Mass %, Max.	ASTM D1742	6	5
Dropping Point, °C, Min.	ASTM D2265	60	>60
Copper Corrosion	ASTM D4048	1a	1a
Feed rate in Set feed Lubricator @30°C, 4,5 Bar, g/h	Rockdrill Test Rig	60 - 90	60 - 90
Base Oil Viscosity @40°C, cSt	ASTM D445	290 - 310	300

All technical data are provided for reference only / SS is available upon request including quality control limits

Performance Levels

• ISO 12924 L-XB(F)AAA00

ALL RIGHTS RESERVED. THIS PRODUCT DATA SHEET (INCLUDING NAME, INFORMATION, LOGOS, IMAGES, PICTURES AND ICONS) WHICH RELATES OR REFERS TO PETRONAS LUBRICANTS INTERNATIONAL (PLI) IS THE SOLE AND ABSOLUTE PROPERTY OF PLI AND/OR ITS HOLDING COMPANY AND SHALL BE TREATED AS PRIVATE AND CONFIDENTIAL. NO PART OF THIS DOCUMENT MAY BE REPRODUCED, STORED IN A RETRIEVAL SYSTEM OR TRANSMITTED IN ANY FORM OR ANY MEANS (ELECTRONIC, MECHANICAL, RECORDING OR OTHERWISE) WITHOUT THE PERMISSION OF PLI AND/OR ITS HOLDING COMPANY.



PETRONAS GREASE Ca 00

Calcium Grease

Health, Safety and Environment

This product is unlikely to present any significant health and safety hazards when used in the recommended application. Avoid contact with skin. Wash immediately with soap and water after skin contact. Do not discharge into drains, soil or water.

For further detail regarding storage, safe handling, and disposal of product, please refer to product SDS or contact us at: <u>www.pli-petronas.com</u>.

Important Note

The word PETRONAS, the PETRONAS logo and such other related trademarks and/or marks used herein are trademarks or registered trademarks of PETRONAS Lubricants International Sdn. Bhd. ("PLISB"), or its subsidiaries or related Holding Corporation under license unless indicated otherwise. The PLI Documents and the information contained herein are believed to be accurate as of the date of printing. PLISB makes no express or implied representation or warranties as to its accuracy or completeness or information in or any transaction performed. The PLI Documents and information provided are based on standard tests under laboratory conditions and is given only as a guide. Users are advised to ensure that they refer to the latest version of these PLI Documents. It is the responsibility of the users to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations imposed by the respective local authorities.

Safety Data Sheets are available for all our products and should only be consulted for appropriate information regarding storage, safe handling and disposal of the product. No responsibility shall be taken by either PLISB or its subsidiaries and related holding corporation for any loss or injury or any direct, indirect, special, exemplary, consequential damages or any damages whatsoever, whether in action of contract, negligence or other tortuous action, in connection with or resulting from abnormal use of the materials and/or information, from any failure to adhere to recommendations, or from hazards inherent in the nature of the materials and/or information. All products, services and information supplied are under our standard conditions of sale. Please consult with any of our local representatives in the event you require any further information.

ALL RIGHTS RESERVED. THIS PRODUCT DATA SHEET (INCLUDING NAME, INFORMATION, LOGOS, IMAGES, PICTURES AND ICONS) WHICH RELATES OR REFERS TO PETRONAS LUBRICANTS INTERNATIONAL (PLI) IS THE SOLE AND ABSOLUTE PROPERTY OF PLI AND/OR ITS HOLDING COMPANY AND SHALL BE TREATED AS PRIVATE AND CONFIDENTIAL. NO PART OF THIS DOCUMENT MAY BE REPRODUCED, STORED IN A RETRIEVAL SYSTEM OR TRANSMITTED IN ANY FORM OR ANY MEANS (ELECTRONIC, MECHANICAL, RECORDING OR OTHERWISE) WITHOUT THE PERMISSION OF PLI AND/OR ITS HOLDING COMPANY.