

# URANIA FE LS Cod. 1354

## DESCRIPTION

Fully synthetic lubricant developed with IVECO and FPT for Euro V and Euro VI engines fitted with HI-eSCR system, common rail injection, particulate filter and variable geometry turbine. Its low SAPS formulation offers outstanding protection for the particulate filter against combustion residues. High fuel economy properties. It exceeds IVECO 18- 1804 CLASSE TLS E6, C.T.R. I720.I12

## CHARACTERISTICS

Urania FE LS has been developed in co-engineering with IVECO to offer high performance and ultimate protection of the engine. Its particular formulation, obtained as a result of thousands of hours of laboratory, bench and road tests, gives the product extraordinary features:

- | high protection of the particulate filter, thanks to the specific Low SAPS formulation;
- | up to 40% longer life of the DPF;
- | its particular resistance to oxidation allows better performance of the variable geometry turbine, under harsh operating conditions;
- | improves cleanliness and protection of the lubricated engine up to the maximum oil drain intervals specified by IVECO, also in harsh missions;
- | excellent Fuel Economy;
- | easy starting and protection in all climatic conditions.



## ADVICE ON USE

IVECO recommends the use of Urania FE LS for the maximum oil drain intervals on its vehicles and in particular for the Euro V and Euro VI engines fitted with Hi-eSCR system.

## RECOMMENDED BY

IVECO

## TECHNICAL DATA

SAE 5W-30, ACEA E4/E6/E7,  
IVECO 18-1804 CLASSE TLS E6, CONTRACTUAL TECHNICAL REF. No I720.I12,  
DAF: Suitable for normal drain intervals and engines equipped with DPF and where DAF requires ACEA E6.,  
DEUTZ DQC IV-10 LA, MACK EO-N, MAN M3477,  
MB-Approval 228.51, MTU OIL TYPE 3.1,  
RENAULT RVI RXD,RLD/RLD-2,  
SCANIA: Suitable for normal oil drain intervals.,  
VOITH Oil Class: B, VOLVO VDS-3