

TECHNICAL DATA SHEET



PETROL COMPLETE FUEL SYSTEM CLEANER

PRODUCT FEATURES

Gasoline performance additive.

Premium multifunctional additive has been formulated to meet the challenges of direct injection engine technology, whilst continuing to deliver excellent performance in the traditional port fuel injection platform. Cleans the entire fuel system. Protects the discharge valves of modern high performance motors.

- Increased fuel economy
- Improved power and acceleration
- Reduced emissions
- Excellent engine life
- Superior combustion chamber deposit control
- Good demulsibility
- A rating corrosion protection
- Low viscosity for easy handling
- Excellent cold temperature intake valve protection

Compatible with Ethanol (E10)

CHEMICAL AND PHYSICAL PROPERTIES

- Appearance liquidColor Light brown
- Odor tipycal
- Density at 20°C 0,892 g/cm³
- Viscosity (40°C ASTM D1298) 11,36 mm²/s

The reported data are subject to normal manufacturing tolerances

DIRECTIONS FOR USE

For best results use one bottle in a tank (50 litres of gasoline fuel). Repeat every 6500 km (4000 miles)

SHELF LIFE

3 years minimum. Store tightly closed in the original container in a dry area at temperatures between 5 and 40° C. Avoid direct sunlight.

PACKAGING

PVC bottle size: 250 ml

Product code: 9069 – 1D249069 Languages on label: EN/DE/FR

ADDITIONAL INFORMATION

For further information about product safety, please consult safety data sheet.

T.S. 05.07.2019 Rev.1

The data contained herein are the result of technological research by our laboratories and are given for informative purposes only. We exclude any liability deriving from the incorrect choice or application of the product and from the lack of the necessary precautions, which should be carefully checked by the user.

Sistemi di gestione di qualità della società Arexons S.p.A. certificati ISO 9001 da LRQA.

Sistemi di gestione di ambiente e sicurezza della società Arexons S.p.A. certificati ISO 14001 e OHSAS 18001 da Bureau Veritas.