#### **Product Data Sheet**

## PETRONAS GRIS EP/LC



## **Multipurpose Lithium Complex EP Grease**

**PETRONAS Gris EP/LC** is a premium quality multipurpose lithium complex extreme pressure (EP) grease, specially formulated to provide excellent performance for a wide variety of application and severe operating condition.

It is specially manufactured using high viscosity index premium quality base oils thickened with lithium complex soap

#### **Applications**

PETRONAS Gris EP/LC recommended to be used in wide range of industrial, automotive and construction application:

- Uses in automotive and industrial applications where high temperature is required
- Industrial ball and roller bearing.
- Roller element-bearing applications in moist environment.
- High and shock load applications
- Operating temperature range is -15°C to 180°C
- NLGI 2 is recommended for multipurpose applications.

#### Features and Benefits

- Protections against bearing wear under severe condition and shock loading
- Good low and high temperature stability
- Multipurpose usage will minimize inventory cost

#### **Typical Properties**

Characteristics	2
NLGI Grade	2
Soap Type	Lithium Complex
Texture	Smooth
Color	Yellow
Base oil type	Mineral
Oil Viscosity @40 °C, cSt	200
Oil Viscosity @100°C, cSt	18
Worked Penetration @25°C, dmm	283
Dropping Point, °C	280
Oil Separation @100 °C, 24 hrs, %wt	1.2
Water Washout @38°C, 1 hr, %wt	3.1
Timken OK load, lbs	50

<sup>\*</sup> All technical data is provided for reference only.

### **Product Data Sheet**

# PETRONAS GRIS EP/LC



**Multipurpose Lithium Complex EP Grease** 

Health, Safety and Environment

For further assistance on product MSDS, recommendation or technical queries, please liaise with the regional technical services engineer or contact HQ technical engineers.