

# Safety Data Sheet

## PETRONAS GEAR MEP 220

Revision Date: 2/10/2020

version 1



### **SECTION 1: IDENTIFICATION OF THE HAZARDOUS CHEMICAL AND OF THE SUPPLIER**

---

#### 1.1. PRODUCT IDENTIFIER

MIXTURE IDENTIFICATION:

TRADE NAME:

**PETRONAS GEAR MEP 220**

Trade code: 77619

#### 1.2. RECOMMENDED USE OF THE CHEMICAL AND RESTRICTIONS ON USE

RECOMMENDED USE:

Gear fluid

USES ADVISED AGAINST:

This product should not be used for other purposes than those specified without the advice of an expert.

#### 1.3. DETAILS OF THE SUPPLIER

COMPANY:

PETRONAS LUBRICANTS INDIA (Pvt) Limited.

Unit No. 603, C Wing, Corporate Avenue,

Opp. Solitaire Corporate Park,

Chakala, Andheri (East), Mumbai – 400 093

Contact: +91 22 6771 7500, FAX: +91 226725 7457

COMPETENT PERSON FOR SAFETY DATA OF PRODUCT:

Information on the legislation compliance [info-regulation.eu@pli-petronas.com](mailto:info-regulation.eu@pli-petronas.com) (english)

#### 1.4. EMERGENCY PHONE NUMBER

Emergency Answer Service (24h/7d) :

+65 3158 1198

000 800 100 7479 (access from India only)

### **SECTION 2: HAZARD IDENTIFICATION**

---

#### 2.1. CLASSIFICATION OF THE SUBSTANCE OR MIXTURE

0 The product is not classified as dangerous according to GHS.

ADVERSE PHYSICOCHEMICAL, HUMAN HEALTH AND ENVIRONMENTAL EFFECTS:

No other hazards

#### 2.2. LABEL ELEMENTS

The product is not classified as dangerous according to GHS.

# Safety Data Sheet

## PETRONAS GEAR MEP 220

Revision Date: 2/10/2020

version 1



### 2.3. OTHER HAZARDS WHICH DO NOT RESULT IN A CLASSIFICATION

No other hazards

## **SECTION 3: COMPOSITION & INFORMATION OF THE INGREDIENTS OF THE HAZARDOUS CHEMICAL**

### 3.1. SUBSTANCES

N.A.

### 3.2. MIXTURES

Severely refined mineral and/or synthetic oils, additives.

Hazardous components within the meaning of the "GHS" regulation and related classification:

<b>QUANTITY</b>	<b>NAME</b>	<b>IDENT. NUMB.</b>	<b>CLASSIFICATION</b>
0.1-<0.25 %	Reaction products of 4-methyl-2-pentanol and diphosphorus pentasulfide, propoxylated, esterified with diphosphorus pentaoxide, and salted by amines, C12-14- tert-alkyl	EC:931-384-6	Acute Tox. 4, H302; Eye Dam. 1, H318; Skin Sens. 1B, H317; Aquatic Acute 2, H401; Aquatic Chronic 2, H411
0.05-<0.1 %	1,3,4-Thiadiazolidine-2,5-dithione, reaction products with hydrogen peroxide and tert-nonanethiol	CAS:91648-65-6 EC:293-927-7	Aquatic Chronic 3, H412
0.05-<0.1 %	(Z)-octadec-9-enylamine	CAS:112-90-3 EC:204-015-5 Index:612-283-00-3	Acute Tox. 4, H302; Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Asp. Tox. 1, H304; Eye Dam. 1, H318; Skin Corr. 1B, H314; STOT RE 2, H373; STOT SE 3, H335, M-Chronic:10, M-Acute:10

90.0-100.0 % Not dangerous oils

H-phrases and list of abbreviations: see heading 16.

## **SECTION 4: FIRST-AID MEASURES**

### 4.1. DESCRIPTION OF NECESSARY FIRST-AID MEASURES

#### IN CASE OF INGESTION:

Do not induce vomiting to avoid aspiration into the respiratory tracts. Wash out thoroughly the mouth with water. Obtain immediate medical attention.

#### IN CASE OF EYES CONTACT:

Rinse thoroughly with plenty of water for at least 10 minutes keeping eyelids open. Remove contact

# Safety Data Sheet

## PETRONAS GEAR MEP 220

Revision Date: 2/10/2020

version 1



lenses if this can be done easily. Obtain medical attention in case of development and persistence of pain and redness. In case of contact with hot product, rinse thoroughly with plenty of water to dissipate heat. Obtain immediate medical attention to assess eye conditions and the correct treatment to be practiced.

### IN CASE OF SKIN CONTACT:

Remove contaminated clothes and shoes and rinse thoroughly with plenty of water and soap.

### IN CASE OF INHALATION:

Expose affected person to fresh air and obtain medical attention if necessary.

#### 4.2. MOST IMPORTANT SYMPTOMS/EFFECTS, ACUTE AND DELAYED

Refer to section 11.

#### 4.3. INDICATION OF IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT NEEDED, IF NECESSARY

Refer to section 4.1.

### **SECTION 5: FIRE-FIGHTING MEASURES**

---

#### 5.1. EXTINGUISHING MEDIA

This product has no special fire risk. In case of fire use foam, carbon dioxide, dry chemical powder and water mist.

Cool down with water the containers don't get involved in fire to avoid their possible explosion.

Avoid high pressure water jet. Use water jet only to cool down surfaces exposed to fire.

#### SUITABLE EXTINGUISHING MEDIA:

Water.

Carbon dioxide (CO<sub>2</sub>).

#### UNSUITABLE EXTINGUISHING MEDIA:

None in particular.

#### 5.2. SPECIAL HAZARDS ARISING FROM THE CHEMICAL

Don't breathe combustion fumes: fire can form harmful compounds.

Do not inhale explosion and combustion gases.

Burning produces heavy smoke.

HAZARDOUS COMBUSTION PRODUCTS: Oxides of carbon, compounds of sulphur, phosphorus, nitrogen and products of incomplete combustion.

#### 5.3. SPECIAL PROTECTIVE ACTIONS FOR FIRE-FIGHTERS

Use suitable breathing apparatus .

Move undamaged containers from immediate hazard area if it can be done safely.

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

### **SECTION 6: ACCIDENTAL RELEASE MEASURES**

---

# Safety Data Sheet

## PETRONAS GEAR MEP 220

Revision Date: 2/10/2020

version 1



### 6.1. PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES

Avoid ingestion of product. Avoid contact with skin and eyes by wearing appropriate protective clothing. Avoid to breathe fumes and aerosols.

Surfaces on which the product has been spilled may become slippery.

Wear personal protection equipment.

See protective measures under point 7 and 8.

### 6.2. ENVIRONMENTAL PRECAUTIONS

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

Retain contaminated washing water and dispose it.

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

### 6.3. METHODS AND MATERIAL FOR CONTAINMENT AND CLEANING UP

Avoid flame and/or spark near leak and produced waste. Do not smoke. In case of large spills dike, absorb and shovel up into suitable containers for disposal. Contain small spills with absorbent material. Put dirty material in suitable container. Dispose of dirty material in accordance with local or national regulations.

See also section 8 and 13

## **SECTION 7: HANDLING AND STORAGE**

---

### 7.1. PRECAUTIONS FOR SAFE HANDLING

Avoid ingestion. Avoid frequent and prolonged skin contact and contact with eyes. Provide adequate ventilation to avoid mist or aerosol. Don't smoke or use open flames; avoid contact with spark or other sources of ignition. Don't work near open container to avoid high concentration of vapours. Don't eat or drink during use.

### 7.2. CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES

Store under cover in the original container securely closed away from heat and sources of ignition. Do not store in the open air. Assure a correct ventilation of premises and the control of possible leak. Keep out of flame or spark and avoid the accumulation of electrostatic charges. Keep out of reach of children and away from food and drink.

Storage class (TRGS 510, Germany): 9

Refer to the uses listed in Section 1.2.

## **SECTION 8: EXPOSURE CONTROLS AND PERSONAL PROTECTION**

---

### 8.1. CONTROL PARAMETERS

# Safety Data Sheet

## PETRONAS GEAR MEP 220

Revision Date: 2/10/2020

version 1



OEL: oil mists - TLV/TWA (8 h) : 5 mg/m<sup>3</sup> - TLV/STEL: 10 mg/m<sup>3</sup>

Predicted No Effect Concentration (PNEC) values

COMPONENT	CAS-NO.	PNEC LIMIT	EXPOSURE ROUTE	EXPOSURE FREQUENCY	REMARK
1,3,4-Thiadiazolidine-2,5-dithione, reaction products with hydrogen peroxide and tert-nonanethiol	91648-65-6	0.041 mg/l	Fresh Water		
		380.620 mg/kg	Air		
		0.004 mg/l	Fresh Water		
		908.960 mg/kg	Marine water sediments		

Derived No Effect Level. (DNEL)

COMPONENT	CAS-NO.	WORKER INDUSTRIAL EXPOSURE	WORKER PROFESSIONAL EXPOSURE	CONSUMER EXPOSURE	EXPOSURE ROUTE	EXPOSURE FREQUENCY	REMARK
1,3,4-Thiadiazolidine-2,5-dithione, reaction products with hydrogen peroxide and tert-nonanethiol	91648-65-6	4408.000 mg/m <sup>3</sup>			Human Inhalation	Long Term, systemic effects	

### 8.2. INDIVIDUAL PROTECTION MEASURES, SUCH AS PERSONAL PROTECTIVE EQUIPMENT (PPE)

#### TECHNICAL PRECAUTIONS:

Avoid production and diffusion of mist and aerosol with utilization of localized ventilation/aspiration or other required precautions. Adopt all required precaution to avoid product immission in environment (e.g., blasting systems, catch basins, ...).

#### RESPIRATORY PROTECTION:

None required under normal conditions of use. Use approved full face respirator with organic vapour filter cartridge if the recommended exposure limits are exceeded.

#### EYE PROTECTION:

Chemical goggles and face shield in case of oil splashes.

#### PROTECTION FOR HANDS:

Wear suitable gloves (i.e. neoprene, nitrile). Gloves should be changed when they show wear. The kind of gloves and the term of use must be decided from employer with regard to processing and to allow for DPI legislation and glove producer's indications. Wear gloves only with clean hands.

# Safety Data Sheet

## PETRONAS GEAR MEP 220

Revision Date: 2/10/2020

version 1



### PROTECTION FOR SKIN:

Wear suitable protective clothing; change it immediately in case of large contamination and wash it before subsequent use.

Practice reasonable personal cleanliness.

### ENVIRONMENTAL EXPOSURE CONTROLS:

Refer to technical precautions and also to sections 6.2, 6.3, 7.2, 12 and 13.

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

---

CHEMICAL-PHYSICAL PROPERTY	VALUE	METHOD
PHYSICAL STATE	LIQUID	
APPEARANCE AND COLOUR	VISCOUS	
ODOUR	NOT RELEVANT	
ODOUR THRESHOLD	NOT RELEVANT	
PH	N.A.	
MELTING POINT / FREEZING POINT	N.A.	
INITIAL BOILING POINT AND BOILING RANGE	>300 °C (572 °F)	( ASTM D1120 )
FLASH POINT	237 °C (459 °F)	( ASTM D92 )
EVAPORATION RATE	N.A.	
UPPER/LOWER FLAMMABILITY OR EXPLOSIVE LIMITS	N.A.	
VAPOUR DENSITY	N.A.	
VAPOUR PRESSURE	N.A.	
DENSITY	0.8904 g/cm <sup>3</sup>	( ASTM D4052 )
SOLUBILITY IN WATER	IMMISCIBLE	
SOLUBILITY IN OIL	N.A.	
PARTITION COEFFICIENT (N-OCTANOL/WATER)	N.A.	
AUTO-IGNITION TEMPERATURE	N.A.	
DECOMPOSITION TEMPERATURE	N.A.	
KINEMATIC VISCOSITY AT 100°C	N.A.	
KINEMATIC VISCOSITY AT 40°C	220.6 cSt	( ASTM D445 )
EXPLOSIVE PROPERTIES	N.A.	
OXIDIZING PROPERTIES	N.A.	
FLAMMABILITY (SOLID, GAS):	N.A.	

## SECTION 10: STABILITY AND REACTIVITY

---

### 10.1. REACTIVITY

Read carefully all information provided in other sections of heading 10.

### 10.2. CHEMICAL STABILITY

The product is stable under normal conditions of use.

### 10.3. POSSIBILITY OF HAZARDOUS REACTIONS

# Safety Data Sheet

## PETRONAS GEAR MEP 220

Revision Date: 2/10/2020

version 1



Not expected under normal conditions of use.

### 10.4. CONDITIONS TO AVOID

This product must be kept far from heat sources. In any case, avoid exposing product to temperatures above the flash point.

### 10.5. INCOMPATIBLE MATERIALS

Strong oxidizing agents, hard acids and bases.

### 10.6. HAZARDOUS DECOMPOSITION PRODUCTS

Oxides of carbon, compounds of sulphur, phosphorus, nitrogen and hydrogen sulfide.

## **SECTION 11: TOXICOLOGICAL INFORMATION**

---

### 11.1. INFORMATION ON TOXICOLOGICAL EFFECTS

#### ACUTE TOXICITY:

This product is not classified in this hazard class.

Unlike to cause harm if accidentally swallowed in small doses, though ingestion of large quantities may cause gastro-intestinal effects.

#### SKIN CORROSION OR IRRITATION:

This product is not classified in this hazard class, but prolonged or repeated skin contact sometimes may cause irritations and dermatitis.

#### SERIOUS EYE DAMAGE OR EYE IRRITATION:

This product is not classified in this hazard class, but direct contact may cause slight irritations.

#### RESPIRATORY SENSITIZATION:

This product is not classified in this hazard class.

#### SKIN SENSITIZATION:

This product is not classified in this hazard class.

#### GERM CELL MUTAGENICITY:

Based on available data, the classification criteria are not met.

#### CARCINOGENICITY:

Based on available data, the classification criteria are not met.

#### REPRODUCTIVE TOXICITY:

Based on available data, the classification criteria are not met.

# Safety Data Sheet

## PETRONAS GEAR MEP 220

Revision Date: 2/10/2020

version 1



### SPECIFIC TARGET ORGAN TOXICITY (STOT) – SINGLE EXPOSURE:

This product is not classified in this hazard class, but inhalation of mists and vapours generated at elevated temperatures sometimes may cause respiratory irritation.

### SPECIFIC TARGET ORGAN TOXICITY (STOT) – REPEATED EXPOSURE:

This product is not classified in this hazard class.

### ASPIRATION HAZARD:

This product is not classified in this hazard class.

Toxicological information on main components of the mixture: No Data Available

## SECTION 12: ECOLOGICAL INFORMATION

### 12.1. TOXICITY

#### Eco-Toxicological Information:

This product is not classified dangerous for the environment.

#### List of components with eco-toxicological properties

COMPONENT	IDENT. NUMB.	ECOTOX INFOS
Reaction products of 4-methyl-2-pentanol and diphosphorus pentasulfide, propoxylated, esterified with diphosphorus pentoxide, and salted by amines, C12-14- tert-alkyl	EINECS: 931-384-6	a) Aquatic acute toxicity : LC50 Fish = 8.50000 mg/L 96h b) Aquatic chronic toxicity : NOEC Fish = 3.20000 mg/L 96h a) Aquatic acute toxicity : EC50 Daphnia = 91.40000 mg/L 48h b) Aquatic chronic toxicity : NOEC Daphnia 0.12000 mg/L - 21 d a) Aquatic acute toxicity : EC50 Daphnia 0.66000 mg/L - 21 d a) Aquatic acute toxicity : EC50 Algae = 6.40000 mg/L 96h b) Aquatic chronic toxicity : NOEC Algae = 1.70000 mg/L 96h
1,3,4-Thiadiazolidine-2,5-dithione, reaction products with hydrogen peroxide and tert-nonanethiol	CAS: 91648-65-6 - EINECS: 293-927-7	a) Aquatic acute toxicity : LC50 Fish > 1.00000 mg/L 96h b) Aquatic chronic toxicity : NOEC Fish = 1.00000 mg/L 96h a) Aquatic acute toxicity : EC50 Daphnia = 41.00000 mg/L



# Safety Data Sheet

## PETRONAS GEAR MEP 220

Revision Date: 2/10/2020

version 1



48h

b) Aquatic chronic toxicity : NOEC Daphnia = 32.00000 mg/L  
48h

b) Aquatic chronic toxicity : NOEC Algae = 100.00000 mg/L  
72h

a) Aquatic acute toxicity : EC50 Algae > 100.00000 mg/L 72h

(Z)-octadec-9-enylamine

CAS: 112-90-3 - EINECS:  
204-015-5 -  
INDEX: 612-  
283-00-3

a) Aquatic acute toxicity : LC50 Fish = 0.11000 mg/L 96h

a) Aquatic acute toxicity : EC50 Daphnia = 0.01100 mg/L 48h  
b) Aquatic chronic toxicity : NOEC Daphnia = 0.01300 mg/L -  
21 d

a) Aquatic acute toxicity : EC50 Algae > 0.10000 mg/L 72h

### 12.2. PERSISTENCE AND DEGRADABILITY

Data on biodegradability of product are not available.

no data available

### 12.3. BIOACCUMULATIVE POTENTIAL

Not available.

no data available

### 12.4. MOBILITY IN SOIL

As the dispersion in the environment may result in contamination of environmental matrix (soil, subsoil, surface water and groundwater), do not release in the environment

no data available

### 12.5. OTHER ADVERSE EFFECTS

Not available.

No Components with environmental hazard properties found.

## **SECTION 13: DISPOSAL CONSIDERATIONS**

---

### 13.1. DISPOSAL METHODS

Prevent contamination of soil, drains and surface waters. Do not discharge in sewers, tunnels or water courses. Dispose in accordance with local or national regulations via authorised person/licensed waste disposal contractor.

The used product is to be considered a special waste to be classified in accordance with the local

# Safety Data Sheet

## PETRONAS GEAR MEP 220

Revision Date: 2/10/2020

version 1



legislation on waste.

Recover, if possible. Send to authorised disposal plants or for incineration under controlled conditions. In so doing, comply with the local and national regulations currently in force.

### SECTION 14: TRANSPORT INFORMATION

---

#### 14.1. UN NUMBER

N/A

#### 14.2. UN PROPER SHIPPING NAME

ADR-Shipping Name: N/A

IATA-Technical name: N/A

IMDG-Technical name: N/A

#### 14.3. TRANSPORT HAZARD CLASS(ES)

ADR-Class: N/A

IATA-Class: N/A

IMDG-Class: N/A

#### 14.4. PACKING GROUP, IF APPLICABLE

ADR-Packing Group: N/A

IATA-Packing group: N/A

IMDG-Packing group: N/A

#### 14.5. ENVIRONMENTAL HAZARDS

Toxic ingredients quantity: 0.00

Very toxic ingredients quantity: 0.00

Marine pollutant: No

Environmental Pollutant: N.A.

#### 14.6. TRANSPORT IN BULK ACCORDING TO ANNEX II OF MARPOL73/78 AND THE IBC CODE

N.A.

#### 14.7. SPECIAL PRECAUTIONS FOR USER

##### Road and Rail (ADR-RID):

ADR-Label: N/A

ADR - Hazard identification number: N/A

ADR-Transport category (Tunnel restriction code): N/A

##### Air (IATA):

# Safety Data Sheet

## PETRONAS GEAR MEP 220

Revision Date: 2/10/2020

version 1



IATA-Passenger Aircraft: N/A  
IATA-Cargo Aircraft: N/A  
IATA-Label: N/A  
IATA-Subsidiary hazards: N/A  
IATA-Erg: N/A  
IATA-Special Provisions: N/A

### Sea (IMDG):

IMDG-Stowage Code: N/A  
IMDG-Stowage Note: N/A  
IMDG-Subsidiary hazards: N/A  
IMDG-Special Provisions: N/A  
IMDG-Page: N/A  
IMDG-Label: N/A  
IMDG-EMS: N/A  
IMDG-MFAG: N/A

## **SECTION 15: REGULATORY INFORMATION**

---

### 15.1. SAFETY, HEALTH AND ENVIRONMENTAL REGULATIONS SPECIFIC FOR THE PRODUCT IN QUESTION

Globally Harmonized System of Classification and Labeling of Chemicals (GHS), Rev. 4th  
Regulation (EC) No 1272/2008, with all National and European related legislations, on classification, labelling and packaging of substances and mixtures (CLP)  
Regulation (EC) No 1907/2006, with all National and European related legislations, concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH)  
Manufacture, Storage and Import of Hazardous Chemical Rules, 1989, as amended on 2000 (MSIHC)  
Hazardous Substances (Classification, Packaging and Labelling) Rules, 2011  
Ozone Depleting Substance (R&C) Rules, 2000

## **SECTION 16: OTHER INFORMATION**

---

The mineral base oils contained in this product are severely refined and are therefore not to be considered as carcinogen. They contain less than 3% DMSO extract according to IP 346 method ("Determination of polycyclic aromatics in unused lubricating base oils and asphaltene free petroleum fractions – Dimethyl sulphoxide extraction refractive index method", Institute of Petroleum, London).  
Sheet complies with the criteria of Global Harmonized System (GHS) standards.

This document was prepared by a competent person who has received appropriate training.

This product must not be used in applications other than recommended without first seeking the advice of the Technical Department.

Date of first edition: 02/10/2020

Revision Date:: 02/10/2020 - version 1

This SDS cancels and replaces any preceding release.

This product must be stored, handled and used according to correct industrial hygienic practices and in

# Safety Data Sheet

## PETRONAS GEAR MEP 220

Revision Date: 2/10/2020

version 1



compliance with laws in force.

The information contained herein is based on the present state of our knowledge and is intended to describe our products from the point of view of safety requirements. It should not therefore be considered as any guarantee of specific properties.

Caption about heading 3 and H-statements:

<b>CODE</b>	<b>DESCRIPTION</b>
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H335	May cause respiratory irritation.
H373	May cause damage to organs through prolonged or repeated exposure .
H400	Very toxic to aquatic life.
H401	Toxic to aquatic life
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Legend to abbreviations and acronyms used in the safety data sheet:

ACGIH: American Conference of Governmental Industrial Hygienists

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.

ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways

ATE: Acute Toxicity Estimate

ATEmix: Acute toxicity Estimate (Mixtures)

BCF: Biological Concentration Factor

BEI: Biological Exposure Index

BOD: Biochemical Oxygen Demand

CAS: Chemical Abstracts Service (division of the American Chemical Society).

CAV: Poison Center

CE: European Community

CLP: Classification, Labeling, Packaging.

CMR: Carcinogenic, Mutagenic and Reprotoxic

COD: Chemical Oxygen Demand

COV: Volatile Organic Compound

CSA: Chemical Safety Assessment

CSR: Chemical Safety Report

DMEL: Derived Minimal Effect Level

DNEL: Derived No Effect Level.

DPD: Dangerous Preparations Directive

DSD: Dangerous Substances Directive

EC50: Half Maximal Effective Concentration

ECHA: European Chemicals Agency

EINECS: European Inventory of Existing Commercial Chemical Substances.

# Safety Data Sheet

## PETRONAS GEAR MEP 220

Revision Date: 2/10/2020

version 1



ES: Exposure Scenario

GefStoffVO: Ordinance on Hazardous Substances, Germany.

GHS: Globally Harmonized System of Classification and Labeling of Chemicals.

IARC: International Agency for Research on Cancer

IATA: International Air Transport Association.

IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

IC50: half maximal inhibitory concentration

ICAO: International Civil Aviation Organization.

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO).

IMDG: International Maritime Code for Dangerous Goods.

INCI: International Nomenclature of Cosmetic Ingredients.

IRCCS: Scientific Institute for Research, Hospitalization and Health Care

KAFH: Keep away from heat

KSt: Explosion coefficient.

LC50: Lethal concentration, for 50 percent of test population.

LD50: Lethal dose, for 50 percent of test population.

LDLo: Leathal Dose Low

N.A.: Not Applicable

N/A: Not Applicable

N/D: Not defined/ Not available

NA: Not available

NIOSH: National Institute for Occupational Safety and Health

NOAEL: No Observed Adverse Effect Level

OSHA: Occupational Safety and Health Administration.

PBT: Persistent, Bioaccumulative and Toxic

PGK: Packaging Instruction

PNEC: Predicted No Effect Concentration.

PSG: Passengers

RID: Regulation Concerning the International Transport of Dangerous Goods by Rail.

STEL: Short Term Exposure limit.

STOT: Specific Target Organ Toxicity.

TLV: Threshold Limiting Value.

TWATLV: Threshold Limit Value for the Time Weighted Average 8 hour day. (ACGIH Standard).

vPvB: Very Persistent, Very Bioaccumulative.

WGK: German Water Hazard Class.