

TECHNISCHE EIGENSCHAPPEN

UNIVERSAL 15W-40

ARTIKELCODE: 2689

TOEPASSING

Universal oils (STOU) for the lubrication of intake diesel engines or turbo-compressed, transmissions, oil immersed brakes and hydraulic systems of tractors and agricultural machinery in general.

SPECIFICATIES

SAE 15W-40, ISO VG 46/68, NH 030 C, API CE, API GL 4, ZF TE-ML 06B,07B,
MIL-L-2104 E Performance, MIL-L-2105 Performance

OMSCHRIJVING TEST

OMSCHRIJVING TEST	METHODE	EENHEID	TYPISCHE WAARDE
VOORKOMEN	--	--	B. & C.
KLEUR	--	--	L 8
DENSITEIT @ 15°C	ASTM D 4052	g/cm ³	0,886
VISCOSITEIT @ 40°C	ASTM D 445	cSt	110
VISCOSITEIT @ 100°C	ASTM D 445	cSt	14
VISCOSITEITINDEX	ASTM D 2270	--	135
VISCOSITY @ -15°C	ASTM D 2602	cPs	3450
T.B.N.	ASTM D 2896	mg KOH/g	11
VLAMPUNT CI. O. C.	ASTM D 92	°C	220
STOLPUNT	ASTM D 97	°C	<-33
SCHUIM @ 24°C	ASTM D 892	cc/s	0

Alle technische informatie wordt als referentie gegeven.