

**PETRONAS**

TECHNISCHE EIGENSCHAPPEN

AMBRA MULTI G**ARTIKELCODE: 2693**

TOEPASSING

Multi-purpose transmission oil (U.T.T.O) for use on tractors, agricultural equipment and earth moving machinery. Suitable for use in traditional gearboxes, Power-Shift and Shuttle-Shift gearboxes, rear transmissions with wet brakes, side final drives, wheel final drives, differentials, hydraulic systems, P.T.U., mechanical and hydrostatic drives, and power steering units.

SPECIFICATIES

SAE 10W-30, API GL 4, MAT 3525, NH 410 B, ZF TE-ML 03 E, ZF TE-ML 05F, ZF TE-ML 17E, ZF TE-ML 21F

OMSCHRIJVING TEST

OMSCHRIJVING TEST	METHODE	EENHEID	TYPISCHE WAARDE
VOORKOMEN	--	--	B. & C.
KLEUR	--	--	L 3
DENSITEIT @ 15°C	ASTM D 4052	g/cm ³	0,875
VISCOSITEIT @ 100°C	ASTM D 445	cSt	9,5
VISCOSITEITINDEX	ASTM D 2270	--	140
VISCOSITEIT @ -25°C	ASTM D 5293	cPs	6300
VLAMPUNT Cl. O. C.	ASTM D 92	°C	210
STOLPUNT	ASTM D 97	°C	< -40
SCHUIM @ 24°C	ASTM D 892	cc/s	0

Alle technische informatie wordt als referentie gegeven.

ONDERZOEK & ONTWIKKELING**09/2017**