

PETRONAS Syntium 7000 Hybrid

0W-16

Developed with °CoolTech+™ technology to maximize the efficiency and power output of most modern engines

With today's smaller, more compact modern engines running hotter than ever, and congested stop/start traffic increasing operating temperatures further, the conditions couldn't be more challenging and hostile for an oil. To achieve maximum thermal efficiency, engines need to stay cool in the face of aggressive heat.

Description and Applications

PETRONAS Syntium 7000 Hybrid 0W-16 is a fully synthetic lubricant formulated with °CoolTech+™ at the cutting edge of our fluid technology. Our technology effectively reduces friction between moving parts to reduce the heat generated, offering enhanced wear protection and optimum engine efficiency for the full drain interval and delivering optimal performance with lower fuel consumption and emissions.

Constantly switching between internal combustion engine (ICE) and electrical power unit places greater stresses and demands on the engine of a hybrid car. If an engine is constantly stopping and starting in this way, the friction between the engine parts increases, which causes excessive heat generation that leads to higher fuel consumption and emissions, increased wear and risk of engine failure. Hybrid vehicles therefore require dedicated lubricants with high wear protection features.

PETRONAS Syntium 7000 Hybrid 0W-16 is a dedicated and suitable for petrol-electric hybrid vehicle. It is formulated to provide protection against low-speed pre-ignition (LSPI) for turbo charged direct injection gasoline powered vehicles and meets the latest API SP specification.

Thanks to our experience in Motorsports, powering the most efficient hybrid engine, we developed PETRONAS Syntium, a complete range of lubricants, to help drivers to maximize every drop of energy.

Benefits

PETRONAS Syntium 7000 Hybrid 0W-16 is engineered with °CoolTech+™ technology to maximize the efficiency and power output of the most modern engines through:

- Ultimate heat management capability to protect the engine from damaging heat and provide optimum lubrication at extremely low temperatures, to maximize engine efficiency and power output – reducing fuel consumption and emissions
- Ultimate protection against bearing wear, especially under high load conditions that could lead to power loss and engine failure - ensuring maximum performance in hybrid vehicles
- Ultimate lube capability to protect against premature wear in the valvetrain, providing vital defense against engine damage that would lead to deterioration in engine performance and increase in emissions
- Ultimate capacity to retain optimum lubricant viscosity, with enhanced protection against timing chain elongation preventing serious engine failure
- Ultimate resistance to engine sludge formation caused by oil degradation. Effectively controls the formation of sludge throughout the engine, ensuring every part of the engine performs at its maximum efficiency, maximizing power conversion and lowering emissions.
- Ultimate protection against LSPI events, to protect critical engine parts and avoid catastrophic engine failures

Approvals, Specifications and Recommendations

Specifications:

- API SP
- ILSAC GF-6B

Note: Always consult your owner's manual to check for recommended viscosity grade and specifications for your specific vehicle

Typical Physical Data

Parameters	Method	Unit	Typical Value
Appearance	-	-	Bright & Clear
Density @15°C	ASTM D 4052	g/cm ³	0.8452
Kinematic Viscosity @100°C	ASTM D 445	mm ² /s (cSt)	7.24
Viscosity Index	ASTM D 2270	-	167
Flash Point COC	ASTM D 92	°C	224
Sulphated Ash	ASTM D 874	%	0.61
TBN	ASTM D 2896	mgKOH/g	7.24
CCS at -35°C	ASTM D5293	mPa·s	4523
Pour Point	ASTM D97	°C	-42

All technical data are provided for reference only. These characteristics are typical of current production. Whilst future production will conform to PLI's specification, variations in these characteristics may occur.

Health, Safety and Environment

This product is unlikely to present any significant health and safety hazards when used in the recommended application. Avoid contact with skin. Wash immediately with soap and water after skin contact. Do not discharge into drains, soil or water.

For further detail regarding storage, safe handling, and disposal of product, please refer to product SDS or contact us at: www.pli-petronas.com

Important Note

The word PETRONAS, the PETRONAS logo and such other related trademarks and/or marks used herein are trademarks or registered trademarks of PETRONAS Lubricants International Sdn. Bhd. ("PLISB"), or its subsidiaries or related Holding Corporation under license unless indicated otherwise. The PLI Documents and the information contained herein is believed to be accurate as of the date of printing. PLISB makes no express or implied representation or warranties as to its accuracy or completeness or information in or any transaction performed. The PLI Documents information provided is based on standard tests under laboratory conditions and is given only as a guide. Users are advised to ensure that they refer to the latest version of these PLI Documents. It is the responsibility of the users to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations imposed by the respective local authorities.

Safety Data Sheets are available for all our products and should only be consulted for appropriate information regarding storage, safe handling and disposal of the product. No responsibility shall be taken by either PLISB or its subsidiaries and related holding corporation for any loss or injury or any direct, indirect, special, exemplary, consequential damages or any damages whatsoever, whether in action of contract, negligence or other tortious action, in connection or resulting from abnormal use of the materials and/or information, from any failure to adhere to recommendations, or from hazards inherent in the nature of the materials and/or information. All products, services and information supplied are under our standard conditions of sale. Please consult with any of our local representative in the event you require any further information.

Code: 70735