

# SELENIA SUSTAINERA WR PURE ENERGY

## 5W-30

SELENIA lubricants have been engineered to take the very best care of your engine's specific needs. With more than 25 years of expertise in fluids and engine technology, we've engineered a range highly advanced lubricants to deliver maximum protection and get the best performance of your vehicle day after day. SELENIA is the lubricant that has paved the way with FCA for 25 years, and today it represents a standard of excellence for everybody.

### Description and Applications

Selenia SUSTAINera WR PURE ENERGY 5W-30 is an advanced synthetic technology lubricant developed in collaboration with Stellantis. It has engineered as a sustainable lubricant that aligns with the SUSTAINera label that covers all the Stellantis's Circular Economy initiatives across the complete vehicle lifecycle.

Fulfilling the needs of a Euro 5 engines, it passes the ACEA C2 specification- certifies the low ash content, which is an indispensable characteristic to protect the particulate filter from residual combustion products that could cause dangerous clogging of the particulate filter.

#### Sustainable features:

- The ingredient of Selenia SUSTAINera engine oil consists of 30% recycled base oil (re-refined base oil), while the packaging contains 50% recycled plastic (excluding the cap & label)

#### Performance and Customer Benefits:

- Products meet the latest FCA specifications and have been approved by Stellantis
- Selenia SUSTAINera engine oil is developed using next-generation technology and utilizes high-quality Group 3 recycled base oil. It provides exceptional engine protection performance without compromising on product quality. By using Selenia SUSTAINera engine oil, customers can reduce routine maintenance costs, improve operational efficiency, and contribute to environmental sustainability.

#### Environmental Impact:

- Selenia SUSTAINera engine oil focuses on a circular economy approach to reduce carbon emissions and minimize waste generation. This is achieved through two key approaches:
  - Transforming waste into products through recycled plastic packaging.
  - Repurposing and reusing materials, such as recycled base oil (re-refined base oil)
- Our aim is to contribute to a circular future with solutions that can create improved economic and environmental outcomes for our customers and society

### Approvals, Specifications and Recommendations

#### Specifications:

- ACEA C2
- API SP

#### Approvals:

- FCA 955535-S1

Note: Always consult your owner's manual to check for recommended viscosity grade and specifications for your specific vehicle

## Typical Physical Data

Parameters	Method	Unit	Typical Value
<b>Appearance</b>	-	-	Clear
<b>Density at 15°C</b>	ASTM D4052	g/cm <sup>3</sup>	0.8520
<b>Viscosity at 100°C</b>	ASTM D445	cSt	9.744
<b>Viscosity Index</b>	ASTM D2270	-	154
<b>Flash Point Cl. O. C.</b>	ASTM D92	°C	218
<b>T.B.N.</b>	ASTM D2896	mgKOH/g	8.71
<b>Pour Point</b>	ASTM D97	°C	-48

All technical data are provided for reference only. These characteristics are typical of current production. Whilst future production will conform to PLI's specification, variations in these characteristics may occur.

## Health, Safety and Environment

This product is unlikely to present any significant health and safety hazards when used in the recommended application. Avoid contact with skin. Wash immediately with soap and water after skin contact. Do not discharge into drains, soil or water.

For further details regarding storage, safe handling, and disposal of product, please refer to product SDS.

## Important Note

The word PETRONAS, the PETRONAS logo and such other related trademarks and/or marks used herein are trademarks or registered trademarks of PETRONAS Lubricants International Sdn. Bhd. ("PLISB"), or its subsidiaries or related Holding Corporation under license unless indicated otherwise. The PLI Documents and the information contains herein is believed to be accurate as of the date of printing. PLISB makes no express or implied representation or warranties as to its accuracy or completeness or information in or any transaction performed. The PLI Documents information provided is based on standard tests under laboratory conditions and is given only as a guide. Users are advised to ensure that they refer to the latest version of these PLI Documents. It is the responsibility of the users to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations imposed by the respective local authorities.

Safety Data Sheets are available for all our products and should only be consulted for appropriate information regarding storage, safe handling and disposal of the product. No responsibility shall be taken by either PLISB or its subsidiaries and related holding corporation for any loss or injury or any direct, indirect, special, exemplary, consequential damages or any damages whatsoever, whether in action of contract, negligence or other tortuous action, in connection or resulting from abnormal use of the materials and/or information, from any failure to adhere to recommendations, or from hazards inherent in the nature of the materials and/or information. All products, services and information supplied are under our standard conditions of sale. Please consult with any of our local representative in the event you require any further information.

Code: 71010