



PETRONAS

TECHNICAL DATA SHEET

PETRONAS
DURANCE

PETROL POWER BOOSTER

PRODUCT FEATURES

Octane Booster is for universal use and increases the research octane number (RON) of the fuel by 3-4 points, depending on the RON.

- Excellent fuel system deposit control
- Provides maximum valve seat protection
- Protects the catalytic converter
- Improves engine performance and acceleration
- Lowers fuel consumption
- No harmful side effects

PACKAGING

PVC bottle
size: 250 ml

Product code: 9071 – 1D459071
Languages on label: EN/DE/FR

ADDITIONAL INFORMATION

For further information about product safety please consult Safety Data Sheets.

CHEMICAL AND PHYSICAL PROPERTIES

- | | |
|-------------------------------|-------------------------|
| • Appearance | liquid |
| • Colour | Light brown |
| • Odour | typical |
| • Density at 20°C | 0,815 g/cm ³ |
| • Viscosity (40°C ASTM D1298) | < 2 mm ² /s |

The reported data are subject to normal manufacturing tolerances

DIRECTIONS FOR USE

For best results use one bottle in a tank (40 ÷ 50 litres of gasoline fuel).

SHELF LIFE

3 years minimum. Store tightly closed in the original container in a dry area at temperatures between 5 and 40°C. Avoid direct sunlight.

T.S. 05.07.2019

The data contained herein are the result of technological research by our laboratories and are given for informative purposes only. We exclude any liability deriving from the incorrect choice or application of the product and from the lack of the necessary precautions, which should be carefully checked by the user.

Product of PETRONAS LUBRICANTS INTERNATIONAL

Produced by:

AREXONS S.p.A.

Via Antica di Cassano, 23 - 20063 Cernusco sul Naviglio (MI) - Italy

Tel. +39-02-924361 www.petronasdurance.com

Sistemi di gestione di qualità della società Arexons S.p.A.
certificati ISO 9001 da LRQA.

Sistemi di gestione di ambiente e sicurezza della società Arexons S.p.A.
certificati ISO 14001 e OHSAS 18001 da Bureau Veritas.