

Product Data Sheet

Revised: 2021/11/03 (version 1.0)



PETRONAS

PETRONAS Tutela Coolant Premix

Designed to be the Fluid Technology Solutions of choice providing excellent protection and longer fluid life for Vehicle cooling systems

Description and Applications

PETRONAS Tutela Coolant Premix is a high quality ready to use conventional Coolant delivering optimized performance and component durability for heavy-duty engines cooling systems. Formulated with Mono-Ethylene Glycol enhanced with a special Inorganic Acid corrosion inhibitor Technology with nitrites, borates and silicates (IAT Technology), free of phosphates and amines, it provides protection against overheating, frost and corrosion. Suitable for passenger cars, commercial vehicles and off-road machineries where a conventional coolant technology is required.

Benefits

PETRONAS Tutela Coolant Premix enhances your vehicle availability while significantly reducing your operating costs through:

- **Long Cooling System Life** driven by:
 - o Effective corrosion resistance to protect metal-based components
 - o Protection against freezing when outside temperature is down to -38°C (-36.4°F)*
 - o Protection against boiling in case of circuit temperature up to 125°C (257°F)*
 - o Elastomer and plastic compatibility for a longer component's life
- **Enhanced heat transfer properties to prevent overheating**

*With 1 bar (15 psi) radiator cap

Approvals, Specifications and Recommendations

Specifications:

- AFNOR NFR 15-601
- AS 2108-2004
- ASTM D 3306
- ASTM D 6210
- BS 6580:2010
- CUNA 956-16
- ONORM V 5123
- SAE J1034
- SANS 1251:2005
- SH 0521-1999

Performance Level:

- Chrysler MS-9769
- CNHi MAT 3620 (IAT)
- Daimler/Mercedes-Benz 325.0
- Fiat 9.55523
- IVECO 18-1830
- MTU MTL 5048
- John Deere JDM H 24
- Ford WSS-M97B51-A1

Note: Always consult your owner's manual to check recommendation for your specific vehicle

Typical Physical Data

Parameters	Method	Unit	Typical Value
Color	-	-	Yellow
Relative Density @15°C	ASTM D 1122	g/cm ³	1.065
pH	ASTM D 1287	-	6.5
Reserve alkalinity	ASTM D 1121	ml	8.5
Boiling point	ASTM D 1120	°C	108
Freezing point	ASTM D 1177	°C	<-38
Glassware corrosion test	ASTM D1384	-	PASS

All technical data are provided for reference only. These characteristics are typical of current production. Whilst future production will conform to PLI's specification, variations in these characteristics may occur.

Health, Safety and Environment

This product is unlikely to present any significant health and safety hazards when used in the recommended application. Avoid contact with skin. Wash immediately with soap and water after skin contact. Do not discharge into drains, soil or water.

For further detail regarding storage, safe handling, and disposal of product, please refer to product SDS or contact us at: www.pli-petronas.com

Important Note

The word PETRONAS, the PETRONAS logo and such other related trademarks and/or marks used herein are trademarks or registered trademarks of PETRONAS Lubricants International Sdn. Bhd. ("**PLISB**"), or its subsidiaries or related Holding Corporation under license unless indicated otherwise. The data sheet and the information contained herein is believed to be accurate as of the date of printing. PLISB makes no express or implied representation or warranties as to its accuracy or completeness or information in or any transaction performed. The PLI Documents information provided is based on standard tests under laboratory conditions and is given only as a guide. Users are advised to ensure that they refer to the latest version of these PLI Documents. It is the responsibility of the users to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations imposed by the respective local authorities.

Safety Data Sheets are available for all our products and should be only be consulted for appropriate information regarding storage, safe handling and disposal of the product. No responsibility shall be taken by either PLISB or its subsidiaries and related holding corporation for any loss or injury or any direct, indirect, special, exemplary, consequential damages or any damages whatsoever, whether in action of contract, negligence or other tortious action, in connection or resulting from abnormal use of the materials and/or information, from any failure to adhere to recommendations, or from hazards inherent in the nature of the materials and/or information. All products, services and information supplied are under our standard conditions of sale. Please consult with any of our local representative in the event you require any further information.

Code: 81040