

TECHNICAL DATA SHEET



DIESEL TMF Diesel Multifunction Treatment

- PRODUCT DESCRIPTION

Petronas Durance DIESEL TMF is a multifunction additive for diesel fuel for cars and heavy-duty vehicles, diesel and turbo diesel.

Used regularly all year round, the product improves the efficiency of the engine, extending its useful life; it thoroughly cleans and descales injectors, improves the performance of the engine and the power, raising the cetane number of the diesel fuel.

It impedes wear on the pump, even with low sulfur content diesel.

- It ensures the necessary lubrication of the diesel pump.
- It cleans and protects the injection system from deposits and corrosion.
- It improves combustion.
- It reduces smoke and exhaust fumes.
- It aids cold starts.
- It reduces engine noise.
- Chlorine free.

- FIELDS OF USE

For all engines fueled with diesel.

- TECHNICAL CHARACTERISTICS

•	Appearance	Liquid
•	Color	Straw-yellow
•	Odor	Typical
•	Density at 15°C ASTM D1298	0,822 g/ml
•	Viscosity at 40°C ASTM D445	$2 \text{ mm}^2/\text{s}$
•	Flash Point	>65°C

- METHOD OF USE

Pour the product directly into the tank after refueling. To maintain the product performance specifications, repeat the treatment about every 2000 km.

- DOSAGE

250 ml package is sufficient for the treatment of 50 liters of diesel.

- STORAGE

Unopened and stored at room temperature away from direct sunlight, for at least 3 years.

- PACKAGING

PVC bottle 250 ml

Product code: 9073 – 1D479073 Languages on label: EN/DE/FR

- NOTES

For information on product safety, please consult Material Safety Data Sheet.

T.S. 05.07.2019

The data contained herein are the result of technological research by our laboratories and are given for informative purposes only. We exclude any liability deriving from the incorrect choice or application of the product and from the lack of the necessary precautions, which should be carefully checked by the user.