



PETRONAS

# Technical Data Sheet

Revised: 2017/01/09 (version 1.0)

# PETRONAS Sprinta F900

# 10W-40

## APPLICATIONS

Suitable for all types of 4-stroke gasoline motorcycle engines, clutches and gear boxes especially for high performance 4-stroke motorcycle engines. Also suitable for portable power equipment engines requiring JASO MA2 or MA, API SN lubricants. It is suitable for motorcycles manufactured by leading Japanese, European and American manufacturers operating under normal to severe riding conditions.

Note: Always consult your owner's manual to check recommended viscosity grade and specifications for your particular vehicle.

## SPECIFICATIONS & APPROVALS\*

Meets or Exceeds the requirements of:	API SN
	JASO MA2
	Also meet JASO MA

\* All technical data is provided for reference only.

## TYPICAL PHYSICAL DATA\*\*

Parameters	Method	Unit	Typical Value
Appearance	-	-	B&C
Density 15 <sup>0</sup> C	ASTM D 4052	g/cm <sup>3</sup>	0.862
Viscosity at 100 <sup>0</sup> C	ASTM D 445	cSt	14.5
Viscosity Index	ASTM D 2270	-	190
Flash Point Cl. O. C	ASTM D 92	<sup>0</sup> C	240
Pour Point	ASTM D 97	<sup>0</sup> C	-42
Foam at 24 <sup>0</sup> C	ASTM D 892	ml	0/0
Sulphated Ash	ASTM D 874	%	0.8

\*\* These characteristics are typical of current production. Whilst future production will conform to PLI's specification, variations in these characteristics may occur.

## FEATURES & BENEFITS

- Exceptional oil film strength to withstand shear stress, delivering excellent bike responsiveness and gives your bike a longer life.
- Exceptional control in deposit build ups especially under high operating temperature. Helps maintaining bike power.
- Exceptional oxidation resistance and low volatility, providing potential extended drainage interval.
- Helps eliminate clutch slippage and enhances clutch performance, delivering exceptional drivability.
- Provides exceptional engine, gear & clutch protection.
- Synthetic technology base fluid enabling wide temperature operation, delivering protection at start up and effectively lubricates under high temperature

## OIL TYPE

Fully synthetic

## Health, Safety and Environment

This product is unlikely to present any significant health and safety hazards when used in the recommended application. Avoid contact with skin. Wash immediately with soap and water after skin contact. Do not discharge into drains, soil or water.

For further detail regarding storage, safe handling, and disposal of product, please refer to product SDS or contact us at: [www.pli-petronas.com](http://www.pli-petronas.com)

## Important Note

The word PETRONAS, the PETRONAS logo and such other related trademarks and/or marks used herein are trademarks or registered trademarks of PETRONAS Lubricants International Sdn. Bhd. (“PLISB”), or its subsidiaries or related Holding Corporation under license unless indicated otherwise. The PLI Documents and the information contained herein is believed to be accurate as of the date of printing. PLISB makes no express or implied representation or warranties as to its accuracy or completeness or information in or any transaction performed. The PLI Documents information provided is based on standard tests under laboratory conditions and is given only as a guide. Users are advised to ensure that they refer to the latest version of these PLI Documents. It is the responsibility of the users to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations imposed by the respective local authorities.

Safety Data Sheets are available for all our products and should be only be consulted for appropriate information regarding storage, safe handling and disposal of the product. No responsibility shall be taken by either PLISB or its subsidiaries and related holding corporation for any loss or injury or any direct, indirect, special, exemplary, consequential damages or any damages whatsoever, whether in action of contract, negligence or other tortious action, in connection or resulting from abnormal use of the materials and/or information, from any failure to adhere to recommendations, or from hazards inherent in the nature of the materials and/or information. All products, services and information supplied are under our standard conditions of sale. Please consult with any of our local representative in the event you require any further information.

Code: 2051