

Technical data sheet

Revision: 26/11/2020 (version 1.0)



PETRONAS Urania DAILY LS 5W-30

Description and applications

PETRONAS Urania DAILY LS 5W-30 is a synthetic-based engine oil developed in collaboration with IVECO and FPT that offers high performance and optimal engine protection. Its unique formulation is the result of thousands of hours of laboratory, bench and road testing.

PETRONAS Urania DAILY LS 5W-30 is recommended for IVECO Daily Euro 5 and Euro V vehicles equipped with particulate filters and variable geometry turbines. Its LOW SAPS formulation provides optimum protection for the particulate filter from combustion residues, offering greater fuel economy benefits.

Approvals, specifications and recommendations

Approvals

- IVECO 18-1811 SC1 C.T.R. N. I510.D09

Note: Always consult the user manual for information on the recommended viscosity grade and specifications for a specific vehicle.

Typical physical data

Parameters	Method	Unit	Typical value
Appearance	--	--	Chiaro e luminoso
Density at 15 °C	ASTM D 5931	g/cm ³	0,85
Kinematic viscosity at 100 °C	ASTM D 445	mm ² /s (cSt)	10,1
Viscosity index	ASTM D 2270	--	>150
Pour point	ASTM D 97	°C	<-36
TBN	ASTM D 2896	mg KOH/g	>7

All technical data is provided for reference purposes only. Typical characteristics of current production. Although future production will comply with PLI specifications, these characteristics are subject to change.

Health, Safety and Environment

This product is unlikely to present any significant health and safety hazards when used in the recommended application. Avoid contact with skin. Wash immediately with soap and water after skin contact. Do not discharge into drains, soil or water.

For further detail regarding storage, safe handling, and disposal of product, please refer to product SDS or contact us at www.pli-petronas.com

Important Note

The word PETRONAS, the PETRONAS logo and such other related trademarks and/or marks used herein are trademarks or registered trademarks of PETRONAS Lubricants International Sdn. Bhd. ("PLISB"), or its subsidiaries or related Holding Corporation under license unless indicated otherwise. The PLI Documents and the information contained herein is believed to be accurate as of the date of printing. PLISB makes no express or implied representation or warranties as to its accuracy or completeness or information in or any transaction performed. The PLI Documents information provided is based on standard tests under laboratory conditions and is given only as a guide. Users are advised to ensure that they refer to the latest version of these PLI Documents. It is the responsibility of the users to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations imposed by the respective local authorities.

Safety Data Sheets are available for all our products and should be only be consulted for appropriate information regarding storage, safe handling and disposal of the product. No responsibility shall be taken by either PLISB or its subsidiaries and related holding corporation for any loss or injury or any direct, indirect, special, exemplary, consequential damages or any damages whatsoever, whether in action of contract, negligence or other tortious action, in connection or resulting from abnormal use of the materials and/or information, from any failure to adhere to recommendations, or from hazards inherent in the nature of the materials and/or information. All products, services and information supplied are under our standard conditions of sale. Please consult with any of our local representative in the event you require any further information..

Cod: 71521