TECHNICAL CHARACTERISTICS

URANIA ECOSYNTH

PRODUCT CODE: 1352

APPLICATION

Synthetic lubricant developed for IVECO for bus and industrial vehicles with CNG engines.

SPECIFICATIONS

SAE 10W-40, ACEA E4/E6/E7, API CI-4,
IVECO 18-1809 CLASSE NG2,CONTRACTUAL TECHNICAL REF. N°I508.N07, DEUTZ DQC IV-10 LA,
MAN 3477, MAN M3271-1, MACK EO-N, VOLVO VDS-3, CAT ECF-1-a Performance, MB 228.51 Level,
MTU TYPE 3.1 Performance, RENAULT RLD, RLD-2, RXD, RGD Performance,
SCANIA LOW ASH Performance

TEST DESCRIPTION

TEST DESCRIPTION	METHOD	UNIT	TYPICAL VALUE
ASPECT	--	--	B. & C.
DENSITY 15°C	ASTM D 4052	g/cm³	0,865
VISCOSITA' @ 100°C	ASTM D 445	cSt	14,3
VISCOSITY INDEX	ASTM D 2270	--	160
FLASH POINT Cl. O. C.	ASTM D 92	°C	> 220
T.B.N.	ASTM D 2896	mg KOH/g	13,2
POUR POINT	ASTM D 97	°C	<- 33
FOAM @ 24°C	ASTM D 892	cc/s	TRACES/0

All technical data is provided for reference only.

RESEARCH & DEVELOPMENT 08/2016