

TECHNISCHE EIGENSCHAPPEN

AKCELA NEXPLORE

ARTIKELCODE: 1751

TOEPASSING

Multi-purpose transmission oil (U.T.T.O) for use on tractors, agricultural equipment and earth moving machinery. Suitable for use in traditional gearboxes, Power-Shift and Shuttle-Shift gearboxes, rear transmissions with wet brakes, side final drives, wheel final drives, differentials, hydraulic systems, P.T.U., mechanical and hydrostatic drives, and power steering units.

SPECIFICATIES

MAT 3525

OMSCHRIJVING TEST

OMSCHRIJVING TEST	METHODE	EENHEID	TYPISCHE WAARDE
VOORKOMEN	--	--	B. & C.
KLEUR	--	--	L 3
DENSITEIT @ 15°C	ASTM D 4052	g/cm ³	0,885
VISCOSITEIT @ 100°C	ASTM D 445	cSt	9,5
VISCOSITEITINDEX	ASTM D 2270	--	147
VISCOSITEIT @ -25°C	ASTM D 5293	cPs	6000
VLAMPUNT CI. O. C.	ASTM D 92	°C	210
STOLPUNT	ASTM D 97	°C	< -40
SCHUIM @ 24°C	ASTM D 892	cc/s	10

Alle technische informatie wordt als referentie gegeven.