



PETRONAS Syntium 3000 E

5W-40

Designed with °CoolTech™ technology to fight excessive engine heat

Modern driving conditions such as stop-start driving, idling in traffic jams, acceleration on highways, driving up steep hills and many more put engines under a lot of stress that can lead to excessive heat buildup. Excessive engine heat generation is not limited to a particular country or driving pattern; it is a common issue engines face across the globe.

Description and Applications

PETRONAS Syntium 3000 E 5W-40 is a fully synthetic lubricant that is formulated with °CoolTech™ to fight excessive engine heat. °CoolTech™ targets the critical heat zones – parts that are affected by excessive heat inside the engine – to effectively absorb and transfer excessive heat to regulate temperature within the engine; defending the engine's critical components from damage and loss of performance.

PETRONAS Syntium 3000 E 5W-40 is especially designed for passenger cars using direct injection turbocharged gasoline engines and diesel engines without diesel particulate filters such as Volkswagen, Mercedes Benz and Renault (please refer to the owner's manual). It is also suitable for SUVs, light vans and vehicles, running on biofuels and equipped with emission control devices such as catalytic converters; fuel injectors, multi-valves or turbochargers operating under severe conditions

The experiences gathered by PETRONAS on the F1 circuits and from the most important motoring events and competitions have enabled the development of PETRONAS Syntium - a range of hi-tech lubricants capable of meeting the needs of new generation engines; both on the track and on the road.

Benefits

PETRONAS Syntium 3000 E 5W-40 is formulated with °CoolTech™ to fight excessive engine heat for optimum engine performance and to defend the engine's critical components through:

- Exceptional sludge prevention capability to protect engines from seizing up.
- Exceptional resistance to high temperature oxidation and oil thickening to provide adequate oil supply to the engine and prevent car breakdown.
- Superior protection against premature wear of engine parts.

Approvals, Specifications and Recommendations

Specifications:

- API SN
- ACEA A3/B4

Approvals:

- MB-Approval 229.5
- Porsche A40
- RENAULT RN0700/RN0710
- VW 502.00/505.00

Performance Levels:

- BMW Longlife-01
- GM-LL-B-025

Note: Always consult your owner's manual to check for recommended viscosity grade and specifications for your specific vehicle

Typical Physical Data

Parameters	Method	Unit	Typical Value
Appearance	-	-	Bright & Clear
Density @15°C	ASTM D 4052	g/cm ³	0.857
Kinematic Viscosity @100°C	ASTM D 445	mm ² /s (cSt)	14.7
Viscosity Index	ASTM D 2270	-	172
Flash Point COC	ASTM D 92	°C	230
Sulphated Ash	ASTM D 874	%	1.2
TBN	ASTM D 2896	mgKOH/g	10
CCS at -30°C	ASTM D5293	mPa·s	6120
Pour Point	ASTM D97	°C	-39

All technical data are provided for reference only. These characteristics are typical of current production. Whilst future production will conform to PLI's specification, variations in these characteristics may occur.

Health, Safety and Environment

This product is unlikely to present any significant health and safety hazards when used in the recommended application. Avoid contact with skin. Wash immediately with soap and water after skin contact. Do not discharge into drains, soil or water.

For further detail regarding storage, safe handling, and disposal of product, please refers to product SDS or contact us at: www.pli-petronas.com

Important Note

The word PETRONAS, the PETRONAS logo and such other related trademarks and/or marks used herein are trademarks or registered trademarks of PETRONAS Lubricants International Sdn. Bhd. ("PLISB"), or its subsidiaries or related Holding Corporation under license unless indicated otherwise. The PLI Documents and the information contains herein is believed to be accurate as of the date of printing. PLISB makes no express or implied representation or warranties as to its accuracy or completeness or information in or any transaction performed. The PLI Documents information provided is based on standard tests under laboratory conditions and is given only as a guide. Users are advised to ensure that they refer to the latest version of these PLI Documents. It is the responsibility of the users to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations imposed by the respective local authorities.

Safety Data Sheets are available for all our products and should be only be consulted for appropriate information regarding storage, safe handling and disposal of the product. No responsibility shall be taken by either PLISB or its subsidiaries and related holding corporation for any loss or injury or any direct, indirect, special, exemplary, consequential damages or any damages whatsoever, whether in action of contract, negligence or other tortuous action, in connection or resulting from abnormal use of the materials and/or information, from any failure to adhere to recommendations, or from hazards inherent in the nature of the materials and/or information. All products, services and information supplied are under our standard conditions of sale. Please consult with any of our local representative in the event you require any further information.

Code: 70134