



PETRONAS

TECHNICAL DATA SHEET

PETRONAS
DURANCE

DIESEL
ANTI FREEZE

PRODUCT FEATURES

Petronas Durance Diesel Antifreeze has been developed to improve diesel fuel fluidity at low temperatures and to prevent setting of wax crystals. Prevents the crystallization of paraffin clogging the filter.

Protects from the crystallisation of paraffin at temperature as low as -20°C depending on the type of diesel fuel. Eliminates the effects of possible contamination of the fuel with water.

Compatible with biofuels

CHEMICAL AND PHYSICAL PROPERTIES

- Appearance liquid
- Colour Light brown
- Odour typical
- Density at 20°C 0,901 g/cm³
- Viscosity (40°C ASTM D1298) 9 mm²/s

The reported data are subject to normal manufacturing tolerances

DIRECTIONS FOR USE

For best results use one bottle in a tank (40 ÷ 50 litres of diesel fuel).

SHELF LIFE

3 years minimum. Store tightly closed in the original container in a dry area at temperatures between 5 and 40°C. Avoid direct sunlight.

PACKAGING

PVC bottle
size: 250 ml.

Product code: 9068 – 1D439068

Languages on label: EN/DE/FR

ADDITIONAL INFORMATION

For further information about product safety, please consult Material Safety Data Sheets.

T.S. 05.07.2019

The data contained herein are the result of technological research by our laboratories and are given for informative purposes only. We exclude any liability deriving from the incorrect choice or application of the product and from the lack of the necessary precautions, which should be carefully checked by the user.

Product of PETRONAS LUBRICANTS INTERNATIONAL

Produced by:

AREXONS S.p.A.

Via Antica di Cassano, 23 - 20063 Cernusco sul Naviglio (MI) - Italy

Tel. +39-02-924361 www.petronasdurance.com

Sistemi di gestione di qualità della società Arexons S.p.A.
certificati ISO 9001 da LRQA.

Sistemi di gestione di ambiente e sicurezza della società Arexons S.p.A.
certificati ISO 14001 e OHSAS 18001 da Bureau Veritas.